

INDUSTRIAL COMPONENT DATA

1SDA062939R1 ABB T7L 1250 PR232/P LSI In 1250A 4p F F

Brand: ABB | Manufacturer Part Number: 1SDA062939R1



Manufacturer	ABB
MPN / Reference	1SDA062939R1
Catalog number	062939
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-B4722E6EFF
Generated	2026-08-05

Product Overview

T7L 1250 PR232/P LSI In=1250A 4p F F
T7L1250 PR232/P LSI 4P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Molded case "Isomax-Tmax" > T7
--------------	--------------------------------------

Additional Product Information

ABB EcoSolutions
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK10103A1059
9AKK108467A6707
Ordering
EAN 8015644654887
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions

Product Net Width 280 mm

Product Net Height 268 mm

Product Net Depth / Length 154 mm

Product Net Weight 12.5 kg

Container Information

Package Level 1 Units 1 piece

Package Level 1 Width 360 mm

Package Level 1 Height 350 mm

Package Level 1 Depth / Length 360 mm

Package Level 1 Gross Weight 14 kg

Package Level 1 EAN 8015644654887

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Suitable For T7

Suitable for Product Class Moulded Case Circuit Breakers

Version F

Technical

Electrical Durability 2000 cycle

60 cycles per hour

Mechanical Durability 10000 cycle

60 cycles per hour

Number of Poles 4P

Power Loss at Rated Operating Conditions per Pole 47 W

Rated Current (In) 1250 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 690 V AC

Rated Service Short-Circuit Breaking Capacity (Ics) (220 V AC) 200 kA

(230 V AC) 200 kA

(380 V AC) 120 kA

(400 V AC) 120 kA

(415 V AC) 120 kA

(440...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA062939R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.