

INDUSTRIAL COMPONENT DATA

1SDA065296R1 ABB T7L1200 PR332/P-LSI R1200 Im18000 3PFFUL

Brand: ABB | Manufacturer Part Number: 1SDA065296R1



Manufacturer	ABB
MPN / Reference	1SDA065296R1
Catalog number	065296
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-84D82C9E34
Generated	2026-08-04

Product Overview

T7L1200 PR332/P-LSI R1200 Im18000 3PFFUL

T7L 1200 UL PR332/P LSI In1200A 3p FF

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax"

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK10103A1059

9AKK108467A6707

Ordering

Order Code US and Canada T7L1200RW

EAN 8015644681081

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 210 mm

Product Net Height 268 mm

Product Net Depth / Length 154 mm

Product Net Weight 9.7 kg

Container Information

Package Level 1 EAN 8015644681081

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Suitable For T7

Suitable for Product Class Moulded Case Circuit Breakers

Version F

Technical

Mechanical Durability 10000 cycle

60 cycles per hour

Number of Poles 3P

Power Loss at Rated Operating Conditions per Pole 47 W

Rated Current (In) 1200 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 630 V AC

Rated Uninterrupted Current (Iu) 1200 A

Release PR332/P LSI

Release Type EL

Short-Circuit Performance Level L

Standards UL

Sub-type T7

Terminal Connection Type Fixed Circuit-Breakers

Front

Test Voltage Max (Utest) 3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489 (240 V AC) 150 kA

(480 V AC) 100 kA

(600 V AC) 65 kA

C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA065296R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.