

INDUSTRIAL COMPONENT DATA

1SDA063022R1 ABB T7S 1600 PR332/P LSI In 1600A 4p F F M

Brand: ABB | Manufacturer Part Number: 1SDA063022R1



Manufacturer	ABB
MPN / Reference	1SDA063022R1
Catalog number	063022
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-4346B1B5DB
Generated	2026-08-06

Product Overview

T7S 1600 PR332/P LSI In=1600A 4p F F M
T7S1600 PR332/P LSI 4P F F M

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax" > T7

Additional Product Information

ABB EcoSolutions
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK10103A1059
9AKK108467A6707
Ordering
Order Code US and Canada T7MSFC4AR000000XX
EAN 8015644655716
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090

Dimensions

Product Net Width 280 mm

Product Net Height 268 mm

Product Net Depth / Length 178 mm

Product Net Weight 14 kg

Container Information

Package Level 1 Units 1 piece

Package Level 1 Width 360 mm

Package Level 1 Height 350 mm

Package Level 1 Depth / Length 360 mm

Package Level 1 Gross Weight 15.5 kg

Package Level 1 EAN 8015644655716

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Suitable For T7M

Suitable for Product Class Moulded Case Circuit Breakers

Version F**Technical**

Electrical Durability 2000 cycle

60 cycles per hour

Mechanical Durability 10000 cycle

60 cycles per hour

Number of Poles 4P

Power Loss at Rated Operating Conditions per Pole 77 W

Rated Current (In) 1600 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 690 V AC

Rated Service Short-Circuit Breaking Capacity (Ics) (220 V AC) 85 kA

(230 V AC) 85 kA

(380 V AC) 50 kA...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend ABB / 1SDA063022R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.