

INDUSTRIAL COMPONENT DATA

1SDA065755R1 ABB T8D 2500 4p F F

Brand: ABB | Manufacturer Part Number: 1SDA065755R1



Manufacturer	ABB
MPN / Reference	1SDA065755R1
Catalog number	065755
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-9DD6FFBF15
Generated	2026-08-01

Product Overview

T8D 2500 4p F F

T8D2500 4P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax" > T8 and Accessories

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK107046A3003

9AKK108467A6707

Ordering

EAN 8015644686666

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 553 mm

Product Net Height 382 mm

Product Net Depth / Length 282 mm

Product Net Weight 12.5 kg

Container Information

Package Level 1 Units 1 piece

Package Level 1 Width 650 mm

Package Level 1 Height 475 mm

Package Level 1 Depth / Length 695 mm

Package Level 1 Gross Weight 14 kg

Package Level 1 EAN 8015644686666

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Switch Disconnecter

Version F

Technical

Electrical Durability 4000 cycle

20 cycles per hour

Mechanical Durability 15000 cycle

60 cycles per hour

Number of Poles 4P

Power Loss at Rated Operating Conditions per Pole 73 W

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 690 V AC

Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 40 A

Rated Uninterrupted Current (Iu) 2500 A

Short-Circuit Performance Level D

Standards IEC

Sub-type T8

Terminal Connection Type Fixed Circuit-Breakers

Front

Certificates and Declarations....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA065755R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.