

INDUSTRIAL COMPONENT DATA

1SDA065756R1 ABB T8D 3200 3p F VR

Brand: ABB | Manufacturer Part Number: 1SDA065756R1



Manufacturer	ABB
MPN / Reference	1SDA065756R1
Catalog number	065756
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-D82196245F
Generated	2026-08-03

Product Overview

T8D 3200 3p F VR

T8D3200 3P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax" > T8 and Accessories

Additional Product Information

ABB EcoSolutions

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

Toxic Substances Control Act - TSCA 9AKK108467A8326

Environmental

Environmental Information 9AKK107046A3003

9AKK108467A6707

Ordering

EAN 8015644686673

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 427 mm
Product Net Height 382 mm
Product Net Depth / Length 282 mm
Product Net Weight 100 kg
Container Information
Package Level 1 Units 1 piece
Package Level 1 Width 525 mm
Package Level 1 Height 665 mm
Package Level 1 Depth / Length 695 mm
Package Level 1 Gross Weight 108 kg
Package Level 1 EAN 8015644686673
Additional Information
Product Main Type SACE Tmax T
Product Name Moulded Case Circuit Breaker
Product Type Switch Disconnecter
Version F
Technical
Electrical Durability 3000 cycle
20 cycles per hour
Mechanical Durability 15000 cycle
60 cycles per hour
Number of Poles 3P
Power Loss at Rated Operating Conditions per Pole 117 W
Rated Impulse Withstand Voltage (Uimp) 8 kV
Rated Insulation Voltage (Ui) 1000 V
Rated Operational Voltage 690 V AC
Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 40 A
Rated Uninterrupted Current (Iu) 3200 A
Short-Circuit Performance Level D
Standards IEC
Sub-type T8
Terminal Connection Type Fixed Circuit-Breakers
Rear flat Vertical
Certificates and...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA065756R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.