

INDUSTRIAL COMPONENT DATA

1SDA065758R1 ABB T8L 2500 PR331/P LSI In 2500A 3p F F

Brand: ABB | Manufacturer Part Number: 1SDA065758R1



Manufacturer	ABB
MPN / Reference	1SDA065758R1
Catalog number	065758
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-D6B17C0D47
Generated	2026-08-03

Product Overview

T8L 2500 PR331/P LSI In=2500A 3p F F
T8L2500 PR331/P LSI 3P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Molded case "Isomax-Tmax" > T8 and Accessories**

Additional Product Information

Circular Value
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK107046A3003
9AKK108467A6707
REACH Declaration 9AKK108466A1425
RoHS Information 9AKK108466A1424
RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Ordering
Order Code US and Canada T8LFE3HC000000XX
EAN 8015644686697
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090
Dimensions

Product Net Width 427 mm
Product Net Height 382 mm
Product Net Depth / Length 282 mm
Product Net Weight 64 kg
Container Information
Package Level 1 Units 1 piece
Package Level 1 Width 525 mm
Package Level 1 Height 475 mm
Package Level 1 Depth / Length 695 mm
Package Level 1 Gross Weight 69 kg
Package Level 1 EAN 8015644686697
Additional Information
Electrical Durability 4000 cycle
20 cycles per hour
Mechanical Durability 15000 cycle
60 cycles per hour
Number of Poles 3
Power Loss at Rated Operating Conditions per Pole 73 W
Product Main Type SACE Tmax T
Product Name Moulded Case Circuit Breaker
Product Type Automatic Circuit Breaker
Rated Current (In) 2500 A
Rated Impulse Withstand Voltage (Uimp) 8 kV
Rated Insulation Voltage (Ui) 1000 V
Rated Operational Voltage 690 V AC
Rated Service Short-Circuit Breaking Capacity (Ics) (220 V AC) 85 kA
(230 V AC) 85 kA
(380 V AC) 85 kA
(400 V AC) 85 kA
(415 V AC) 85 kA
(440 V AC) 85 kA
(500 V AC) 65 kA
(690 V AC) 50 kA
Rated Short-time Withstand Current Low...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA065758R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.