


INDUSTRIAL COMPONENT DATA

1SAZ421201R1002 ABB TA200DU-110 Thermal Overload Relay

Brand: ABB | Manufacturer Part Number: 1SAZ421201R1002



Manufacturer	ABB
MPN / Reference	1SAZ421201R1002
Catalog number	421201
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-54D196E6F4
Generated	2026-08-01

Product Overview

TA200DU-110 Thermal Overload Relay
TA200DU110 THERMAL RELAY 80-110A
TA200DU-110 Thermal Overload Relay 80 ... 110 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Contactors and overload relays > Thermal Relays**

Additional Product Information

Ordering

Minimum Order Quantity 1 piece
Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202
Instructions and Manuals 2CDC106028M6802
Instructions and Manuals (Part 2) 1SAC200017M0002
Time-Current Characteristic Curve 1SAZ400502F0002
CAD Dimensional Drawing 2CDC001079B0201
Dimension Diagram 1SAZ400401F0001

Dimensions

Product Net Width 104 mm
Product Net Height 151 mm

Product Net Depth / Length 126 mm

Product Net Weight 0.76 kg

Technical

Setting Range 80 ... 110 A

Rated Operational Voltage Auxiliary Circuit 440 V DC

Auxiliary Circuit 500 V AC

Main Circuit 690 V AC

Main Circuit 440 V DC

Rated Operational Current (Ie) 110 A

Rated Frequency (f) Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Main Circuit 60 Hz

Main Circuit 50 Hz

Main Circuit DC

Rated Impulse Withstand Voltage (Uimp) Auxiliary Circuit 6 kV

Main Circuit 6 kV

Rated Insulation Voltage (Ui) 690 V

Number of Poles 3P

Number of Auxiliary Contacts NC 1

Number of Auxiliary Contacts NO 1

Number of Protected Poles 3

Conventional Free-air Thermal Current (Ith) Auxiliary Circuit NC 5 A

Auxiliary Circuit NO 5 A

Rated Operational Current AC-15 (Ie) (120 V) NC 3 A

(120 V) NO 1.5 A

(240 V) NC 3 A

(240 V) NO 1.2 A

(400 V) NC 0.75 A

(400 V) NO 0.37 A

(440 V) NC 0.75 A

(440 V) NO 0.37 A

(500 V) NC 0.3 A

(500 V) NO 0.25 A

Rated Operational Current DC-13 (Ie) (125 V) NC 0.25 A

(125 V) NO 0.25 A

(24 V) NC 1.25 A

(24 V) NO 1.25 A

(250 V) NC 0.12 A

(250 V) NO 0.04 A

(60 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAZ421201R1002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.