

INDUSTRIAL COMPONENT DATA

1SBL241022R3610 ABB UA26-30-10 190V 50Hz / 220V 60Hz Contactor

Brand: ABB | Manufacturer Part Number: 1SBL241022R3610



Manufacturer	ABB
MPN / Reference	1SBL241022R3610
Catalog number	241022
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-6812C3CC54
Generated	2026-08-05

Product Overview

UA26-30-10 190V 50Hz / 220V 60Hz Contactor

UA26-30-10 CONT. condens. 20kVAr 190V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > "A" FRCTLP

Additional Product Information

Ordering

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85364900

Popular Downloads

Data Sheet, Technical Information: 1SBC101140C0203

Instructions and Manuals: FPTC407722P0001

Dimensions

Product Net Width: 54 mm

Product Net Depth / Length: 93.6 mm

Product Net Height: 90 mm

Product Net Weight: 0.6 kg

Technical

Number of Main Contacts NO: 3

Number of Main Contacts NC: 0

Number of Auxiliary Contacts NO: 1
Number of Auxiliary Contacts NC: 0
Rated Operational Voltage: Main Circuit 690 V
Rated Frequency (f): Supply Circuit 50 Hz
Supply Circuit 60 Hz
Conventional Free-air Thermal Current (I_{th}): acc. to IEC 60947-5-1, $\theta = 40\text{ °C}$ 16 A
Rated Operational Current AC-15 (I_e): (220 / 240 V) 4 A
(24 / 127 V) 6 A
(380 / 440 V) 3 A
(500 V) 2 A
(690 V) 2 A
Short-Circuit Protective Devices: Auxiliary Circuit - gG Type Fuses 10 A
gG Type Fuses 1.5 ... 1.8 A
Maximum Breaking Capacity: $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100\text{ A}$) at 440 V 420 A
 $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100\text{ A}$) at 690 V 170 A
Rated Operational Current DC-13 (I_e): (125 V) 1.1 / 138 A
(24 V) 6 / 144 A
(250 V) 0.55 / 138 A
(48 V) 2.8 / 134 A
(72 V) 2 / 144 A
Rated Insulation Voltage (U_i): acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V
acc. to UL/CSA 600 V
Rated Impulse Withstand Voltage (U_{imp}): 8 kV
Maximum Mechanical Switching Frequency: 3600 cycles per hour
Rated Control Circuit Voltage (U_c): 50 Hz 190 V
60 Hz 220 V
Coil Consumption: Pull-in at Max. Rated Control Circuit Voltage 50 Hz 120 V·A
Pull-in at Max. Rated...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL241022R3610 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.