

**INDUSTRIAL COMPONENT DATA**

# 1SBL241024R8410 ABB UA26-30-10RA 110V 50Hz / 110-120V 60Hz Contactor

Brand: ABB | Manufacturer Part Number: 1SBL241024R8410



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | ABB                 |
| MPN / Reference | 1SBL241024R8410     |
| Catalog number  | 241024              |
| Category        | Capacitor contactor |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-CD1084C993       |
| Generated       | 2026-08-06          |

## Product Overview

UA26-30-10RA 110V 50Hz / 110-120V 60Hz Contactor

UA26-30-10RA CONT. condens. 22kVAr 110Va

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                                   |
|--------------|---------------------------------------------------|
| Catalog path | ABB > Contactors and overload relays > "A" FRCTLP |
|--------------|---------------------------------------------------|

## Additional Product Information

### Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

### Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101002M5501

CAD Dimensional Drawing 2CDC001079B0201

### Dimensions

Product Net Width 54 mm

Product Net Depth / Length 126.3 mm

Product Net Height 120 mm

Product Net Weight 0.71 kg

Dimension Diagram FPTE307846

### Technical

Number of Main Contacts NO 3  
Number of Main Contacts NC 0  
Number of Auxiliary Contacts NO 1  
Number of Auxiliary Contacts NC 0  
Number of Poles 3P  
Standards IEC/EN 60947-1, IEC/EN 60947-4-1  
Rated Operational Voltage Auxiliary Circuit 690 V  
Main Circuit 690 V  
Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz  
Control Circuit 50 / 60 Hz  
Main Circuit 50 / 60 Hz  
Conventional Free-air Thermal Current (I<sub>th</sub>) acc. to IEC 60947-5-1,  $\theta = 40\text{ °C}$  16 A  
Rated Operational Current AC-15 (I<sub>e</sub>) (500 V) 2 A  
(690 V) 2 A  
(24 / 127 V) 6 A  
(220 / 240 V) 4 A  
(380 / 400 V) 3 A  
Rated Operational Current DC-13 (I<sub>e</sub>) (24 V) 6 A / 144 W  
(48 V) 2.8 A / 134 W  
(72 V) 2 / 144 W  
(110 V) 1.1 A / 121 W  
(125 V) 1.1 / 138 W  
(220 V) 0.55 A / 121 W  
(250 V) 0.55 / 138 W  
Rated Operational Power AC-6b (P<sub>e</sub>) (230 / 240 V) 40 °C, 50 / 60 Hz 12.5 kvar  
(230 / 240 V) 55 °C, 50 / 60 Hz 11.5 kvar  
(230 / 240 V) 70 °C, 50 / 60 Hz 9 kvar  
(400 / 415 V) 40 °C, 50 / 60 Hz 22 kvar  
(400 / 415 V) 70 °C, 50 / 60 Hz 15.5 kvar  
(400 / 415 V) 55 °C, 50 / 60 Hz 20 kvar  
(440 V) 40 °C, 50 / 60 Hz 24 kvar  
(440 V) 55 °C, 50 / 60 Hz 20 kvar  
(440 V) 70 °C, 50 / 60 Hz 17 kvar  
(...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL241024R8410 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.