


## INDUSTRIAL COMPONENT DATA

# 1SBL281022R8010 ABB UA30-30-10 220-230V 50Hz / 230-240V 60Hz Contactor

Brand: ABB | Manufacturer Part Number: 1SBL281022R8010



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | ABB                 |
| MPN / Reference | 1SBL281022R8010     |
| Catalog number  | 281022              |
| Category        | Capacitor contactor |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-D2998E7C07       |
| Generated       | 2026-08-06          |

## Product Overview

UA30-30-10 220-230V 50Hz / 230-240V 60Hz Contactor

UA30-30-10 CONT. condens. 27.5kVAr 230V

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB &gt; Contactors and overload relays &gt; "A" FRCTLP

## Additional Product Information

## Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

## Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals FPTC407722P0001

CAD Dimensional Drawing 2CDC001079B0201

## Dimensions

Product Net Width 54 mm

Product Net Depth / Length 108.3 mm

Product Net Height 90 mm

Product Net Weight 0.71 kg

## Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0  
Number of Auxiliary Contacts NO 1  
Number of Auxiliary Contacts NC 0  
Number of Poles 3P  
Standards IEC/EN 60947-1, IEC/EN 60947-4-1  
Rated Operational Voltage Auxiliary Circuit 690 V  
Main Circuit 690 V  
Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz  
Control Circuit 50 / 60 Hz  
Main Circuit 50 / 60 Hz  
Conventional Free-air Thermal Current (I<sub>th</sub>) acc. to IEC 60947-5-1,  $\theta = 40\text{ °C}$  16 A  
Rated Operational Current AC-15 (I<sub>e</sub>) (500 V) 2 A  
(690 V) 2 A  
(24 / 127 V) 6 A  
(220 / 240 V) 4 A  
(380 / 400 V) 3 A  
Rated Operational Current DC-13 (I<sub>e</sub>) (24 V) 6 A / 144 W  
(48 V) 2.8 A / 134 W  
(72 V) 2 / 144 W  
(110 V) 1.1 A / 121 W  
(125 V) 1.1 / 138 W  
(220 V) 0.55 A / 121 W  
(250 V) 0.55 / 138 W  
Rated Operational Power AC-6b (P<sub>e</sub>) (230 / 240 V) 40 °C, 50 / 60 Hz 16 kvar  
(230 / 240 V) 55 °C, 50 / 60 Hz 16 kvar  
(230 / 240 V) 70 °C, 50 / 60 Hz 11 kvar  
(400 / 415 V) 40 °C, 50 / 60 Hz 27.5 kvar  
(400 / 415 V) 70 °C, 50 / 60 Hz 19 kvar  
(400 / 415 V) 55 °C, 50 / 60 Hz 27.5 kvar  
(440 V) 40 °C, 50 / 60 Hz 30 kvar  
(440 V) 55 °C, 50 / 60 Hz 30 kvar  
(440 V) 70 °C, 50 / 60 Hz 20 kvar  
(500 / 550 V), 40 °C, 50 / 60 Hz...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL281022R8010 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.