

INDUSTRIAL COMPONENT DATA

UA50-30-00 1SBL351022R1600 ABB UA50-30-00 26V 50Hz / 28V 60Hz Contactor

Brand: ABB | Manufacturer Part Number: UA50-30-00



Manufacturer	ABB
MPN / Reference	UA50-30-00
Catalog number	1SBL351022R1600
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-8FE3D3E035
Generated	2026-08-05

Product Overview

UA50-30-00 26V 50Hz / 28V 60Hz Contactor

UA50-30-00 CONT. condens. 33kVAr 26V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > "A" FRCTLP

Additional Product Information

UA50 3-pole contactors for capacitor switching, can be used for the switching of capacitor banks whose inrush current peaks are less than or equal to 100 times nominal rms current. The table below gives the permissible powers according to operational voltage and temperature close to the contactor. It also specifies the maximum peak current $\hat{I}$ values accepted by the contactor. The capacitors must be discharged (maximum residual voltage at terminals ≤ 50 V) before being re-energized when the contactors are making. In these conditions, electrical durability of contactors is equal to 100 000 operating cycles. The UA.. series 3-pole contactors are of the block type design. - Main poles: 3 main poles - Control circuit: AC operated with laminated magnet circuit - Accessories: a wide range of accessories is available.

Ordering

EAN: 3471522084163

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85369085

Dimensions

Product Net Width: 70mm

Product Net Depth: 108mm

Product Net Height: 110mm

Product Net Weight: 1.160kg

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 140 mm

Package Level 1 Length: 146 mm

Package Level 1 Height: 96 mm

Package Level 1 Gross Weight: 1.16 kg

Package Level 1 EAN: 3471522084163

Package Level 2 Units: 20 piece

Package Level 3 Units: 160 piece

Technical

Number of Main Contacts NO: 3

Number of Main Contacts NC: 0

Number of Auxiliary Contacts NO: 0

Number of Auxiliary Contacts NC: 0

Rated Operational Voltage: Main Circuit 690 V

Shor...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / UA50-30-00 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.