

INDUSTRIAL COMPONENT DATA

1SBL351022R8011 ABB UA50-30-11 220-230V 50Hz / 230-240V 60Hz Contactor

Brand: ABB | Manufacturer Part Number: 1SBL351022R8011



Manufacturer	ABB
MPN / Reference	1SBL351022R8011
Catalog number	351022
Category	Capacitor contactor
Minimum order	1 Pcs
Document ID	EO-44BB980147
Generated	2026-08-06

Product Overview

UA50-30-11 220-230V 50Hz / 230-240V 60Hz Contactor

UA50-30-11 CONT. condens. 33kVAr 230V

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > "A" FRCTLP

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals FPTC407700P0003

Dimensions

Product Net Width 82 mm

Product Net Depth / Length 108 mm

Product Net Height 110 mm

Product Net Weight 1.2 kg

Technical

Number of Main Contacts NO 3

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 1
Number of Auxiliary Contacts NC 1
Number of Poles 3P
Standards IEC/EN 60947-1, IEC/EN 60947-4-1
Rated Operational Voltage Auxiliary Circuit 690 V
Main Circuit 690 V
Rated Frequency (f) Auxiliary Circuit 50 / 60 Hz
Control Circuit 50 / 60 Hz
Main Circuit 50 / 60 Hz
Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-5-1, $\theta = 40\text{ °C}$ 16 A
Rated Operational Current AC-15 (I_e) (500 V) 2 A
(690 V) 2 A
(24 / 127 V) 6 A
(220 / 240 V) 4 A
(380 / 400 V) 3 A
Rated Operational Current DC-13 (I_e) (24 V) 6 A / 144 W
(48 V) 2.8 A / 134 W
(72 V) 1 A / 72 W
(110 V) 0.55 A / 60 W
(125 V) 0.55 A / 69 W
(220 V) 0.30 A / 66 W
(250 V) 0.3 / 75 W
Rated Operational Power AC-6b (P_e) (230 / 240 V) 40 °C, 50 / 60 Hz 20 kvar
(230 / 240 V) 55 °C, 50 / 60 Hz 20 kvar
(230 / 240 V) 70 °C, 50 / 60 Hz 19 kvar
(400 / 415 V) 40 °C, 50 / 60 Hz 33 kvar
(400 / 415 V) 70 °C, 50 / 60 Hz 32 kvar
(400 / 415 V) 55 °C, 50 / 60 Hz 33 kvar
(440 V) 40 °C, 50 / 60 Hz 36 kvar
(440 V) 55 °C, 50 / 60 Hz 36 kvar
(440 V) 70 °C, 50 / 60 Hz 35 kvar
(500 / 550 V), 40 °C, 50 / 60 Hz 40 kvar
(500 / 550 V) 55 °C, 50 / 60 Hz 40 kv...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL351022R8011 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.