

**INDUSTRIAL COMPONENT DATA**

# 1SBL411024R8600 ABB UA75-30-00RA 400-415V 50Hz / 415-440V 60Hz Contactor

Brand: ABB | Manufacturer Part Number: 1SBL411024R8600



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | ABB                 |
| MPN / Reference | 1SBL411024R8600     |
| Catalog number  | 411024              |
| Category        | Capacitor contactor |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-127AD6B1D0       |
| Generated       | 2026-08-06          |

## Product Overview

UA75-30-00RA 400-415V 50Hz / 415-440V 60Hz Contactor

UA75-30-00RA CONT. condens. 60kVAr 400V

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      ABB &gt; Contactors and overload relays &gt; "A" FRCTLP

## Additional Product Information

### Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

### Popular Downloads

Data Sheet, Technical Information 1SBC100214C0202

Instructions and Manuals 1SBC101002M5501

CAD Dimensional Drawing 2CDC001079B0201

### Dimensions

Product Net Width 70 mm

Product Net Depth / Length 140.4 mm

Product Net Height 150 mm

Product Net Weight 1.35 kg

Dimension Diagram FPTE307844

### Technical

Number of Main Contacts NO 3  
Number of Main Contacts NC 0  
Number of Auxiliary Contacts NO 0  
Number of Auxiliary Contacts NC 0  
Number of Poles 3P  
Standards IEC/EN 60947-1, IEC/EN 60947-4-1  
Rated Operational Voltage Main Circuit 690 V  
Rated Frequency (f) Control Circuit 50 / 60 Hz  
Main Circuit 50 / 60 Hz  
Rated Operational Power AC-6b (Pe) (230 / 240 V) 40 °C, 50 / 60 Hz 35 kvar  
(230 / 240 V) 55 °C, 50 / 60 Hz 30 kvar  
(230 / 240 V) 70 °C, 50 / 60 Hz 25 kvar  
(400 / 415 V) 40 °C, 50 / 60 Hz 60 kvar  
(400 / 415 V) 70 °C, 50 / 60 Hz 41 kvar  
(400 / 415 V) 55 °C, 50 / 60 Hz 50 kvar  
(440 V) 40 °C, 50 / 60 Hz 65 kvar  
(440 V) 55 °C, 50 / 60 Hz 53 kvar  
(440 V) 70 °C, 50 / 60 Hz 45 kvar  
(500 / 550 V), 40 °C, 50 / 60 Hz 75 kvar  
(500 / 550 V) 55 °C, 50 / 60 Hz 65 kvar  
(500 / 550 V) 70 °C, 50 / 60 Hz 55 kvar  
(690 V) 40 °C, 50 / 60 Hz 100 kvar  
(690 V) 55 °C, 50 / 60 Hz 80 kvar  
(690 V) 70 °C, 50 / 60 Hz 70 kvar  
Short-Circuit Protective Devices gG Type Fuses 200 A  
Maximum Breaking Capacity  $\cos \phi=0.45$  ( $\cos \phi=0.35$  for  $I_e > 100$  A) at 440 V 1300 A  
 $\cos \phi=0.45$  ( $\cos \phi=0.35$  for  $I_e > 100$  A) at 690 V 630 A  
Rated Insulatio...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBL411024R8600 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.