INDUSTRIAL COMPONENT DATA

GJL1311911R0013 ABB VB7A-30-01-03 Mini Reversing Contactor

Brand: ABB | Manufacturer Part Number: GJL1311911R0013

Manufacturer	ABB
MPN / Reference	GJL1311911R0013
Catalog number	1311911
Category	Combination of contactors
Minimum order	1 Pcs
Document ID	EO-0BBC144950
Generated	2026-08-04

Product Overview

VB7A-30-01-03 Mini Reversing Contactor
VB7A3001 MINI INVERTER 48V 40/450Hz TOR
VB7A-30-01-03 Mini Reversing Contactor 48 V AC - 3 NO - 0 NC - Screw Terminals

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Contactors and overload relays > Minicontactors B6-B7

Additional Product Information

Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85365080
Popular Downloads
EPLAN Data 9AAC205201_EPLAN
Data Sheet, Technical Information 1SBC100214C0202
Instructions and Manuals 2CDC102046M6801
CAD Dimensional Drawing 2CDC001079B0201
Dimensions
Product Net Width 96.2 mm
Product Net Depth / Length 46.7 mm
Product Net Height 57.5 mm
Product Net Weight 0.355 kg

Dimension Diagram GJL1200447F0001
Technical
Number of Main Contacts NO 3
Number of Main Contacts NC 0
Number of Auxiliary Contacts NO 0
Number of Auxiliary Contacts NC 1
Number of Poles 3P
Standards IEC/EN 60947-1
IEC/EN 60947-4-1
IEC/EN 60947-5-1
UL 60947-1
UL 60947-4-1
IEC 60335-2-40 A2L
Rated Operational Voltage Auxiliary Circuit 690 V AC
Auxiliary Circuit 250 V DC
Main Circuit 690 V AC
Main Circuit 220 V DC
Rated Frequency (f) Main Circuit 60 Hz
Main Circuit 50 Hz
Main Circuit DC
Conventional Free-air Thermal Current (Ith) Main Circuit 20 A
Rated Operational Current AC-1 (Ie) (220 / 240 V) 40 °C 20 A
(220 / 240 V) 55 °C 16 A
(380 / 440 V) 40 °C 20 A
(380 / 440 V) 55 °C 16 A
(690 V) 40 °C 6 A
(690 V) 55 °C 6 A
Rated Operational Current AC-3 (Ie) (230 V) 55°C 12 A
(400 V) 55 °C 12 A
(500 V) 55 °C 9 A
(690 V) NO 55°C 3.5 A
Rated Operational Power AC-3 (Pe) (230 V) Three Phase 3 kW
(400 V) Three Phase 5.5 kW
(500 V) Three Phase 5.5 kW
(690 V) Three Phase, NO 3 kW
Rated Breaking Capacity AC-3 8 x Ie / AC-3
Rated Making Capacity AC-3 10 x Ie / AC-3
Rated Short-time Withstand Current Low Voltage (Icw) at 40 °C...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / GJL1311911R0013 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.