

INDUSTRIAL COMPONENT DATA

1SEP600114R0002 ABB Disconnect fuse XLP00 160A 2P

Brand: ABB | Manufacturer Part Number: 1SEP600114R0002



Manufacturer	ABB
MPN / Reference	1SEP600114R0002
Catalog number	600114
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A3BE78782C
Generated	2026-08-05

Product Overview

Disconnect fuse XLP00 160A 2P
XLP00 160A 2P fuse disconnect
XLP00-2P-4BC Fuse Switch Disconnecter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Manual Switches

Additional Product Information

Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Popular Downloads
Data Sheet, Technical Information 1SEC312012D0201
Instructions and Manuals No Instructions and Manuals needed
Environmental
Degree of Protection IP30
Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85389099
Country or Territory of Origin China

Dimensions

Product Net Width 80 mm

Product Net Height 88 mm

Product Net Depth / Length 185 mm

Product Net Weight 0.61 kg

Container Information

Package Level 1 Units shrink-wrap 1 piece

Package Level 1 Width 80 mm

Package Level 1 Depth / Length 185 mm

Package Level 1 Height 88 mm

Package Level 1 Gross Weight 0.61 kg

Package Level 1 EAN 7025840086529

Package Level 2 EAN detach

Technical

Degree of Protection IP30

Device Type Manager (DTM) Fuseswitchdisconnecter

Electronic Fuse Monitoring No

Fuse Size NH00

NH000

Fuse System DIN

Handle Type Front cover 2P

Mounting Type Baseplate

Number of Poles 2P

Power Loss at Rated Load 3.5 W

Rated Conditional Short-Circuit Current (Inc) (690 V) 50 kiloampere rms

Rated Current (In) 160 A

Rated Frequency (f) Main Circuit 50/60 Hz

Rated Impulse Withstand Voltage (Uimp) Main Circuit 8 kV

Rated Operational Current AC-21B (Ie) (690 V) 125 A

Rated Operational Current AC-22B (Ie) (500 V) 160 A

Rated Operational Current DC-22B (220 V) 160 A

Rated Oper...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SEP600114R0002 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.