


INDUSTRIAL COMPONENT DATA

1SDA068183R1 ABB XT1 P FP 3p EF

Brand: ABB | Manufacturer Part Number: 1SDA068183R1



Manufacturer	ABB
MPN / Reference	1SDA068183R1
Catalog number	068183
Category	Chassis part power circuit breaker
Minimum order	1 Pcs
Document ID	EO-4C65CFF752
Generated	2026-07-31

Product Overview

XT1 P FP 3p EF
3P THERMAL PLUG-IN BASE. EF P FP-XT1

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Molded case "Isomax-Tmax" > XT1
--------------	---------------------------------------

Additional Product Information

ABB EcoSolutions
Environmental Product Declaration - EPD 9AKK108469A8952
9AKK108471A0810
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK108467A6707
Ordering
Order Code US and Canada KXT1PFPEF-3
E-Number (Finland) 3640546
E-Number (Norway) 4381502

EAN 8015644020804

Minimum Order Quantity 1 piece

Customs Tariff Number 85389099

Dimensions

Product Net Weight 0.69 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 120 mm

Package Level 1 Height 155 mm

Package Level 1 Depth / Length 190 mm

Package Level 1 Gross Weight 0.79 kg

Package Level 1 EAN 8015644020804

Additional Information

Product Main Type Accessories for Tmax XT

Product Name Accessory

Product Type Fixed Part

Suitable For XT1

Suitable for Product Class SACE Tmax XT

Version P

Technical

Configuration Type Loose or configurable

Number of Poles 3P

Order Multiple 1 piece

Rated Frequency (f) 50 / 60 Hz

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 800 V

Rated Operational Voltage 690 V AC

500 V DC

Rated Uninterrupted Current (Iu) 160 A

Standards IEC60947-2

UL489

Sub-type XT1

Terminal Connection Type Plug-In Circuit-Breakers

Front Extended

Certificates and Declarations

Data Sheet, Technical Inf...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA068183R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.