


**INDUSTRIAL COMPONENT DATA**

# 1SDA068201R1 ABB XT2 W FP 3p HR

Brand: ABB | Manufacturer Part Number: 1SDA068201R1



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | ABB                                |
| MPN / Reference | 1SDA068201R1                       |
| Catalog number  | 068201                             |
| Category        | Chassis part power circuit breaker |
| Minimum order   | 1 Pcs                              |
| Document ID     | EO-14E853AC9B                      |
| Generated       | 2026-07-31                         |

## Product Overview

XT2 W FP 3p HR  
3P TERM REMOVABLE BASE. HR W FP-XT2

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      **ABB > Molded case "Isomax-Tmax" > XT2**

## Additional Product Information

Circular Value  
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658  
Toxic Substances Control Act - TSCA 9AKK108467A8326  
Environmental  
Environmental Information 9AKK108467A6707  
REACH Declaration 9AKK108466A1425  
RoHS Information 9AKK108466A1424  
RoHS Status Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019  
Ordering  
Order Code US and Canada KXT2EWFPHR-3  
E-Number (Finland) 3640814  
EAN 8015644696313  
Minimum Order Quantity 1 piece  
Customs Tariff Number 85389099  
Dimensions

Product Net Weight 1.44 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 145 mm

Package Level 1 Height 155 mm

Package Level 1 Depth / Length 295 mm

Package Level 1 Gross Weight 1.59 kg

Package Level 1 EAN 8015644696313

Additional Information

Configuration Type Loose or configurable

Number of Poles 3

Order Multiple 1 piece

Product Main Type Accessories for Tmax XT

Product Name Accessory

Product Type Fixed Part

Rated Frequency (f) 50 / 60 Hz

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 690 V AC

500 V DC

Rated Uninterrupted Current (Iu) 160 A

Standards IEC60947-2

Sub-type XT2

Suitable For XT2

Suitable for Product Class SACE Tmax XT

Terminal Connection Type Withdrawable Circuit-Breakers

Rear flat Horizontal

Version W

Certificates and Declarations

Data Sheet, Technical Information 1SDC210100D0206

1SDC210099D0206

Declaration of Conformity - CE Refer to the EU Declaration of the relative Circuit Break...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA068201R1 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.