

INDUSTRIAL COMPONENT DATA

1SDA067964R1 ABB XT2L 160 Ekip LSI In 160A 4p F F In 100%

Brand: ABB | Manufacturer Part Number: 1SDA067964R1



Manufacturer	ABB
MPN / Reference	1SDA067964R1
Catalog number	067964
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-F3D7C6EB1B
Generated	2026-08-06

Product Overview

XT2L 160 Ekip LSI In=160A 4p F F In=100%

XT2L160 Ekip LSI R160 4P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax" > XT2

Additional Product Information

C.BREAKER TMAX XT2L 160 FIXED FOUR-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC
EKIP-LSI R 160 A FULLY RATED NEUTRAL

Ordering

EAN:8015644018603

Minimum Order Quantity:1 piece

Customs Tariff Number:85362090

Dimensions

Product Net Width:120mm

Product Net Height:130mm

Product Net Depth:82.5mm

Product Net Weight:1.6kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:130 mm

Package Level 1 Height:208 mm

Package Level 1 Length:145 mm

Package Level 1 Gross Weight:1.6 kg

Package Level 1 EAN:8015644018603

Additional Information

Circuit Breaker Type to be Associated:Power distribution

Electrical Durability:120 cycles per hour

8000 cycle

Mechanical Durability:Nr. Operations 240 cycles per hour

Nr. Operations 25000 cycle

Number of Poles:4

Opening Time:CB with SOR 15 ms

CB with UVR 15 ms

Product Main Type:SACE Tmax XT

Product Name:Automatic Circuit Breaker

Product Type:CB

Rated Current (In):160 A

Rated Frequency (f):50 / 60 Hz

Rated Impulse Withstand Voltage (Uimp):8 kV

Rated Insulation Voltage (Ui):1000 V

Rated Operational Voltage:690 V AC

500 V DC

Rated Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 150 kA

(220 V AC) 150 kA

(380 V AC) 120 kA

(415 V AC) 120 kA

(440 V AC) 100 kA

(500 V AC) 60 kA

(690 V AC) 18 kA

Rated Ultimate Short-Circuit Breaking Capacity (Icu):(220 V AC) 150 kA

(230 V AC) 150 kA

(380 V AC) 120 kA

(415 V AC) 120 kA

(440 V AC) 100 kA

(500 V AC) 60 kA

(690 V AC) 18 kA

Rated Uninterrupted Current (Iu):160 A

Rated Voltage (Ur)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA067964R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.