

INDUSTRIAL COMPONENT DATA

1SDA068560R1 ABB CIRCUIT BREAKER TMAX XT4L 250 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE..

Brand: ABB | Manufacturer Part Number: 1SDA068560R1



Manufacturer	ABB
MPN / Reference	1SDA068560R1
Catalog number	068560
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-955ED3B069
Generated	2026-08-06

Product Overview

CIRCUIT BREAKER TMAX XT4L 250 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC EKIP-I R 250 A
XT4L250 Ekip I R250 3P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax"

Additional Product Information

Ordering

EAN: 8015644024666

Minimum Order Quantity: 1 piece

Customs Tariff Number: 85362090

Dimensions

Product Net Width: 105 mm

Product Net Height: 160 mm

Product Net Depth / Length: 82,5 mm

Product Net Weight: 2,05 kg

Container Information

Package Level 1 Units: 1 piece

Package Level 1 Width: 145 mm

Package Level 1 Height: 210 mm

Package Level 1 Depth / Length: 168 mm

Package Level 1 Gross Weight: 2.5 kg

Package Level 1 EAN: 8015644024666

Additional Information

Circuit Breaker Type to be Associated: Power distribution

Current Type: AC

Electrical Durability: 120 cycles per hour

8000 cycle

Mechanical Durability: Nr. Operations 240 cycles per hour

Nr. Operations 25000 cycle

Number of Poles: 3

Opening Time: CB with SOR 15 ms

CB with UVR 15 ms

Order Multiple: 1 piece

Product Main Type: SACE Tmax XT

Product Name: Moulded Case Circuit Breaker

Product Type: CB

Rated Current (In): 250 A

Rated Frequency (f): 50 / 60 Hz

Rated Voltage (Ur): 690 V

Rated Impulse Withstand Voltage (Uimp): 8 kV

Rated Insulation Voltage (Ui): 1000 V

Rated Operational Voltage: 690 V AC

Rated Service Short-Circuit Breaking Capacity (Ics): (220 V AC) 150 kA

(230 V AC) 150 kA

(240 V AC) 150 kA

(380 V AC) 120 kA

(415 V AC) 120 kA

(440 V AC) 100 kA

(500 V AC) 60 kA

(525 V AC) 50 kA

(690 V AC) 20 kA

Rated Ultimate Short-Circuit Breaking Capacity (Icu): (220 V AC) 150 kA

(230 V AC) 150 kA

(240 V AC) 150 kA

(380 V AC) 120 kA

(415 V AC) 120 kA

(440 V AC) 100 kA

(500 V AC) 60 kA

(525 V AC) 50 kA

(690 V AC) 20 kA

Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SDA068560R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.