

INDUSTRIAL COMPONENT DATA

XT4V250 1SDA068470R1 ABB XT4V 250 MA 200 Im 1000...2000 3p F F

Brand: ABB | Manufacturer Part Number: XT4V250



Manufacturer	ABB
MPN / Reference	XT4V250
Catalog number	1SDA068470R1
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-7269781CF1
Generated	2026-08-05

Product Overview

XT4V 250 MA 200 Im=1000...2000 3p F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Molded case "Isomax-Tmax"
--------------	---------------------------------

Additional Product Information

C.BREAKER TMAX XT4V 250 FIXED THREE-POLE WITH FRONT TERMINALS AND MAGNETIC RELEASE MA Iu 200 A
I3=1000...2000 A

Ordering

EAN:8015644023768

Minimum Order Quantity:1 piece

Customs Tariff Number:85362090

Dimensions

Product Net Width:105mm

Product Net Height:160mm

Product Net Depth:82.5mm

Product Net Weight:2.5kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:145 mm

Package Level 1 Height:210 mm

Package Level 1 Length:168 mm
Package Level 1 Gross Weight:2.5 kg
Package Level 1 EAN:8015644023768
Additional Information
Circuit Breaker Type to be Associated:Motor protection
Electrical Durability:120 cycles per hour
8000 cycle
Mechanical Durability:Nr. Operations 240 cycles per hour
Nr. Operations 25000 cycle
Number of Poles:3
Opening Time:CB with SOR 15 ms
CB with UVR 15 ms
Power Loss:at Rated Operating Conditions per Pole 11.88 W
Product Main Type:SACE Tmax XT
Product Name:Automatic Circuit Breaker
Product Type:CB
Rated Current (In):200 A
Rated Frequency (f):50 / 60 Hz
Rated Impulse Withstand Voltage (Uimp):8 kV
Rated Insulation Voltage (Ui):1000 V
Rated Operational Voltage:690 V AC
500 V DC
Rated Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 200 kA
(220 V AC) 200 kA
(380 V AC) 150 kA
(415 V AC) 150 kA
(440 V AC) 150 kA
(500 V AC) 70 kA
(690 V AC) 20 kA
Rated Ultimate Short-Circuit Breaking Capacity (Icu):(220 V AC) 200 kA
(230 V AC) 200 kA
(380 V AC) 150 kA
(415 V AC) 150 kA
(440 V AC) 150 kA
(500 V AC) 70 kA
(690 V AC) 25 kA
(250 V DC) 2 Pole...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / XT4V250 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.