

INDUSTRIAL COMPONENT DATA

N/D 2TAZ372001R2013 AEG N/D

Brand: AEG | Manufacturer Part Number: #N/D



Manufacturer	AEG
MPN / Reference	#N/D
Catalog number	2TAZ372001R2013
Category	Latching relay
Minimum order	1 Pcs
Document ID	EO-3A5EA5BE7E
Generated	2026-07-31

Product Overview

#N/D

PLS+ C230 Latching Relay 1P -

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path AEG > Power management

Additional Product Information

Extended Product Type:PLS+ C230

Product ID:2TAZ372001R2013

EAN:5413656856177

Catalog Description:PLS+ C230 Latching Relay 1P -

Long Description:Latching relays are electromagnetically operated devices. The range can be used to realise a simple, energy saving and efficient lighting control system. These devices are mainly used in private houses, factory premises and commercial and public buildings as well as in industrial plants. As a rule, latching relays controlled by means of impulse buttons are installed where it is necessary for lighting to be operated from at least three different places. Each time a command is initiated (by means of an impulse button), an electrical pulse is applied to the coil of the latching relay. The coil in the device is briefly energised and activated. That short pulse to the coil leads to the mechanical latch of the internal main contacts. The internal switching mechanism enables us to achieve a safe and reliable interlock (in the same way as a ballpoint pen). Each pulse that is sent to the magnetic coil system switches the device to its previous position where it is held mechanically until the next control pulse is received. The devices are designed for rated currents 16 and 32A. Through the combinable accessories the main modules can be used in nearly all market applications.

Technical

Rated Operational Voltage:250 V AC

Supply Voltage:250 V AC

Rated Current (In):1 A

Frequency (f):Control Voltage 1 50 Hz

Rated Frequency (f):50 Hz

Number of Pole...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send AEG / #N/D with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.