

## INDUSTRIAL COMPONENT DATA

## PD2N-M-DACO DALI2 93452 LUXOMAT PD2N-M-DACO DALI-2

Brand: B.E.G. LUXOMAT | Manufacturer Part Number: PD2N-M-DACO DALI2



|                 |                                    |
|-----------------|------------------------------------|
| Manufacturer    | B.E.G. LUXOMAT                     |
| MPN / Reference | PD2N-M-DACO DALI2                  |
| Catalog number  | PD2N-M-DACO DALI2                  |
| Category        | KNX - Intelligent building systems |
| Minimum order   | 1 unit                             |
| Document ID     | EO-EB15E15908                      |
| Generated       | 2026-07-31                         |

## Product Overview

PD2N-M-DACO DALI2 93452 LUXOMAT PD2N-M-DACO DALI-2

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path B.E.G. LUXOMAT &gt; KNX - Intelligent building systems - B.E.G. LUXOMAT &gt; System devices

## Additional Product Information

## Features

Designation Value

Voltage: 230 V AC  $\pm 10\%$  50 HzDimensions:  $\varnothing$  84 x 85 mm

Power consumption: approx. 2 W

Slave devices: up to 8

Detection area: horizontal 360° (Ceiling mounting)

Range: max.  $\varnothing$  10 m acrossmax.  $\varnothing$  6 m towardsmax.  $\varnothing$  4 m seatedMonitored area (tangential movement): 78 m<sup>2</sup> / 2.5 m mounting height

Mounting height min./max./recommended: 2 m / 5 m / 2.5 m

Degree / class of protection: IP20 / Class II

Impact strength: IK05

Ambient temperature: -25 °C to +50 °C

Housing: polycarbonate, UV-resistant

Material color: white mat, similar to RAL9010

Channel 1 (lighting control)

Designation Value

DALI output: 80 mA (guaranteed), 125 mA (max.), Shut-down mechanism

Supported control gear: DT0, DT5, DT6, DT7

Supported control devices: - (single master)

Follow-up time: 1 min - 150 min

Orientation light: 10 - 30 % / OFF / 5 min - 60 min / ?

Brightness set value: 10 - 2500 Lux

Light measuring: Mixed light measuring

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send B.E.G. LUXOMAT / PD2N-M-DACO DALI2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.