

INDUSTRIAL COMPONENT DATA

PD2N-M-DACO DALI2 93452 LUXOMAT PD2N-M-DACO DALI-2

Brand: B.E.G. LUXOMAT | Manufacturer Part Number: PD2N-M-DACO DALI2



Manufacturer	B.E.G. LUXOMAT
MPN / Reference	PD2N-M-DACO DALI2
Catalog number	PD2N-M-DACO DALI2
Category	KNX - Intelligent building systems
Minimum order	1 unit
Document ID	EO-EB15E15908
Generated	2026-08-02

Product Overview

PD2N-M-DACO DALI2 93452 LUXOMAT PD2N-M-DACO DALI-2

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path B.E.G. LUXOMAT > KNX - Intelligent building systems - B.E.G. LUXOMAT > System devices

Additional Product Information

Features

Designation Value

Voltage: 230 V AC $\pm 10\%$ 50 HzDimensions: $\varnothing$ 84 x 85 mm

Power consumption: approx. 2 W

Slave devices: up to 8

Detection area: horizontal 360° (Ceiling mounting)

Range: max. $\varnothing$ 10 m acrossmax. $\varnothing$ 6 m towardsmax. $\varnothing$ 4 m seatedMonitored area (tangential movement): 78 m² / 2.5 m mounting height

Mounting height min./max./recommended: 2 m / 5 m / 2.5 m

Degree / class of protection: IP20 / Class II

Impact strength: IK05

Ambient temperature: -25 °C to +50 °C

Housing: polycarbonate, UV-resistant

Material color: white mat, similar to RAL9010

Channel 1 (lighting control)

Designation Value

DALI output: 80 mA (guaranteed), 125 mA (max.), Shut-down mechanism

Supported control gear: DT0, DT5, DT6, DT7

Supported control devices: - (single master)

Follow-up time: 1 min - 150 min

Orientation light: 10 - 30 % / OFF / 5 min - 60 min / ?

Brightness set value: 10 - 2500 Lux

Light measuring: Mixed light measuring

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send B.E.G. LUXOMAT / PD2N-M-DACO DALI2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.