

INDUSTRIAL COMPONENT DATA

346020 BTCINO BT/2H-ALIM.SUPPL.0.6 TO 2DIN

Brand: BTCINO | Manufacturer Part Number: 346020



Manufacturer	BTCINO
MPN / Reference	346020
Catalog number	346020
Category	DC-power supply
Minimum order	1 Pcs
Document ID	EO-2A2357A4B3
Generated	2026-08-01

Product Overview

BT/2H-ALIM.SUPPL.0.6 TO 2DIN

BT/2H-ALIM. SULP.0.6A 2DIN

Bticino 2 DIN Additional Power Supply Unit

Supplementary 2-wire feeder 2mod DIN

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTCINO > VIDEO DOOR PHONES**

Additional Product Information

Voltage type (supply voltage) DC

1st secondary output voltage 26.9-27.1 V

Max. output current 1 0.6 A

Secondary voltage adjustable No

Short-circuit-proof Yes

Rated supply voltage AC 50 Hz 220-240 V

Rated supply voltage AC 60 Hz 220-240 V

Output voltage stabilized Yes

Power consumption 41.8 VA

Power output 16.2 W

Stabilized Yes

Type of electric connection Screw connection

Suitable for rail mounting Yes

Suitable for wall mounting No
Suitable for distribution board Yes
Width in number of modular spacings 2
Direct mounting possible No
Width 33.9 mm
Height 89.7 mm
Depth 66.2 mm
Suitable for safety functions No
Degree of protection (IP) IP30
ETIM for 346020 Low-voltage industrial controls and switchgear (EC002540)
Feature Name
Feature Value
Power output (EF003034)
16.2 W
Height (EF000040)
89.7 mm
Degree of protection (IP) (EF005474)
IP30
Wall mounting possible (EF003973)
No
Suitable for safety functions (EF001597)
No
Suitable for rail mounting (EF003972)
Yes
Output voltage stabilized (EF003092)
Yes
Rated supply voltage AC 50 Hz (EF007076)
220 V
Rated supply voltage AC 60 Hz (EF007077)
220 V
Short-circuit-proof (EF007332)
Yes
Max. output current 1 (EF008284)
0.6 A
Modular version (EF001126)
Yes
Voltage type (supply voltage) (EF002991)
DC
Width in number of modular spacings (EF002950)
2
Direct mounting possible (EF005689)
No
Stabilized (EF005302)
Yes
Type of electric connection (EF003961)
Screw connection
1st secondary output voltage (EF006792)

26.9 V

Secondary voltage adjustable (E...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend BTICINO / 346020 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.