

**INDUSTRIAL COMPONENT DATA****AM4191AA BTCINO MX-BASE USBA+A 3A/5V 1M BLAN**

Brand: BTICINO | Manufacturer Part Number: AM4191AA



|                 |                  |
|-----------------|------------------|
| Manufacturer    | BTICINO          |
| MPN / Reference | AM4191AA         |
| Catalog number  | AM4191AA         |
| Category        | USB power supply |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-38BF7E378E    |
| Generated       | 2026-07-29       |

**Product Overview**

MX-BASE USBA+A 3A/5V 1M BLAN

Màtx double charger base - Type A+A - 1 module - White

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**

|              |                            |
|--------------|----------------------------|
| Catalog path | BTICINO > MATIX MECHANISMS |
|--------------|----------------------------|

**Additional Product Information**

## Overview

USB A+A Chargers - 3A/5V - 230 Vac - 15W - Allows fast charging of mobile phones, tablets, smartphones, MP3, MP4 - Standby consumption 0.1 W - Class II TBTS - Supplied without cable - 1 module - White.

## description

Màtx - power bases.specifications

Model Other

Number of USB-A ports 2

Number of USB-C ports 0

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.083 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour White  
RAL number 9003  
Device width 23.4 mm  
Device height 43.6 mm  
Device Depth 41 mm  
Min. depth of the recessed box 40 mm  
Suitable for protection grade (IP) IP40  
Impact resistance IK04  
Antibacterial treatment No  
Wireless No  
Installation Depth 32.5 mm  
Operating Temperature 5-40 °C  
Storage temperature -20-70 °C  
Type of voltage AC  
Nominal Voltage 100-240 V  
Power Delivery No  
Nominal current 0.5-0.5 A  
Neutral Mandatory Yes  
Display of markings on the connection terminals Yes  
Compliant with commissioning tests (1000 V) No  
Halogen-free Yes  
Number of terminals 2  
Terminal capacity 1.5-2.5 mm<sup>2</sup>  
Connection Cable Type Flexible or rigid  
Core cross-section 1.5-2.5 mm<sup>2</sup>  
ETIM for AM4191AA Domestic wiring accessories and controls (EC002949)  
Feature Name  
Feature Value  
Model (EF000010)  
Other  
Mounting method (EF000003)  
Flush mounted  
Suitable for degree of protection (IP) (EF006755)  
IP40  
Connection type (EF000124)  
Screwed terminal  
Operating voltage (EF003983)  
100 V  
Device d...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / AM4191AA with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.