

INDUSTRIAL COMPONENT DATA**HD4285C2 BTCINO AX-BASE USBA+2.4 A/5V 2M WHITE**

Brand: BTICINO | Manufacturer Part Number: HD4285C2



Manufacturer	BTICINO
MPN / Reference	HD4285C2
Catalog number	HD4285C2
Category	USB power supply
Minimum order	5 Pcs
Document ID	EO-ECEF615EDB
Generated	2026-07-29

Product Overview

AX-BASE USBA+2.4 A/5V 2M WHITE

AX-BASE USBA+A 2.4A/5V 2M BLAN

Base charger dual USB Axolute - 2.4 A - 5 V - 230 V - White - 2 modules

Double USB (A) Axolute Charger Base - 2.4A - 5V - 230V - White - 2mod

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **BTICINO > AXOLUTE****Additional Product Information**

Product features

Universal chargers USB - Compliant to the standard IEC 62684-2011-01 - Allow the quick charging of mobile phones, tablets, smartphones, MP3, MP4 - Release space for bases of power - Consumption standby < 0.1 W - Class II TBTS - According to the EEC directive on the harmonization of the standard recharging of portable terminals and the reduction of chargers, mobile - Supplied without cable - 5 V - 230 V Charger double USB 2.400 mA - 2 modules - White General characteristics

Axolute - bases of power

ETIM for HD4285C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF000124)
Screwed terminal
Operating voltage (EF003983)
100 V
Device depth (EF008810)
41.5 mm
Impact strength (EF004293)
IK04
Anti-bacterial treatment (EF023790)
No
Number of ports USB-C (EF017049)
0
Min. depth of built-in installation box (EF012278)
40 mm
Output voltage (EF003933)
5 V
Power consumption (EF000346)
0.068 W
Device width (EF008808)
45.1 mm
Device height (EF008809)
45 mm
Colour (EF000007)
White
Number of ports USB-A (EF000997)
2
RAL-number (EF000116)
9003
Max. output current (EF001315)
3000 mA
Frequency (EF000416)
50 Hz

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / HD4285C2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.