

INDUSTRIAL COMPONENT DATA**HS4285C2 BTCINO AX-BASE USBA+2.4 A/5V 2M ANTR**

Brand: BTICINO | Manufacturer Part Number: HS4285C2



Manufacturer	BTICINO
MPN / Reference	HS4285C2
Catalog number	HS4285C2
Category	USB power supply
Minimum order	5 Pcs
Document ID	EO-E2FA03A222
Generated	2026-07-28

Product Overview

AX-BASE USBA+2.4 A/5V 2M ANTR

Base charger dual USB Axolute - 2.4 A - 5 V - 230 V - Anthracite - 2 modules

Double USB (A) Axolute Charger Base - 2.4A - 5V - 230V - Anthracite - 2mod

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **BTICINO > AXOLUTE****Additional Product Information**

Product features

Universal chargers USB - Compliant to the standard IEC 62684-2011-01 - Allow the quick charging of mobile phones, tablets, smartphones, MP3, MP4 - Release space for bases of power - Consumption standby < 0.1 W - Class II TBTS - According to the EEC directive on the harmonization of the standard recharging of portable terminals and the reduction of chargers, mobile - Supplied without cable - 5 V - 230 V Charger double USB 2.400 mA - 2 modules - Anthracite General characteristics

Axolute - bases of power

ETIM for HS4285C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted

Suitable for degree of protection (IP) (EF006755)

IP40

Connection type (EF000124)

Screwed terminal

Operating voltage (EF003983)

100 V

Device depth (EF008810)

41.5 mm

Impact strength (EF004293)

IK04

Anti-bacterial treatment (EF023790)

No

Number of ports USB-C (EF017049)

0

Min. depth of built-in installation box (EF012278)

40 mm

Output voltage (EF003933)

5 V

Power consumption (EF000346)

0.068 W

Device width (EF008808)

45.1 mm

Device height (EF008809)

45 mm

Colour (EF000007)

Anthracite

Number of ports USB-A (EF000997)

2

RAL-number (EF000116)

7015

Max. output current (EF001315)

3000 mA

Frequency (EF000416)

50 Hz

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / HS4285C2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.