

**INDUSTRIAL COMPONENT DATA**

# HS4286C2 BTCINO AX-USB CRADLE (C+C 3A/5V 2M ANTR

Brand: BTCINO | Manufacturer Part Number: HS4286C2



|                 |                  |
|-----------------|------------------|
| Manufacturer    | BTCINO           |
| MPN / Reference | HS4286C2         |
| Catalog number  | HS4286C2         |
| Category        | USB power supply |
| Minimum order   | 10 Pcs           |
| Document ID     | EO-CB21309478    |
| Generated       | 2026-08-01       |

## Product Overview

AX-USB CRADLE (C+C 3A/5V 2M ANTR

AX-BASE USB C+C 3A/5V 2M ANTR

Base USB charger (C+C) Axolute - 3 To - 5 V - 230 V - 2 modules - Anthracite

USB (C+C) Axolute Charger Base - 3A - 5V - 230V - 2mod - Anthracite

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **BTCINO > AXOLUTE**

## Additional Product Information

**Product features**

Universal chargers USB - Compliant to the standard IEC 62684-2011-01 - Allow the quick charging of mobile phones, tablets, smartphones, MP3, MP4 - Release space for bases of power - Consumption standby < 0.1 W - Class II TBTS - According to the EEC directive on the harmonization of the standard recharging of portable terminals and the reduction of chargers, mobile - Supplied without cable - 5 V - 230 V - Charger dual-USB 3 A - Type C + C - 2 modules - Anthracite

**General characteristics**

Axolute - USB chargers

ETIM for HS4286C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted  
Suitable for degree of protection (IP) (EF006755)  
IP40  
Connection type (EF000124)  
Screwed terminal  
Operating voltage (EF003983)  
100 V  
Device depth (EF008810)  
42 mm  
Impact strength (EF004293)  
IK04  
Anti-bacterial treatment (EF023790)  
No  
Number of ports USB-C (EF017049)  
2  
Output voltage (EF003933)  
5 V  
Power consumption (EF000346)  
0.064 W  
Device width (EF008808)  
45.1 mm  
Device height (EF008809)  
45 mm  
Colour (EF000007)  
Anthracite  
Number of ports USB-A (EF000997)  
0  
RAL-number (EF000116)  
7015  
Max. output current (EF001315)  
3000 mA  
Frequency (EF000416)  
50 Hz

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / HS4286C2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.