

INDUSTRIAL COMPONENT DATA

K4005TL BTCINO LN-PULS W/DOOR CONTACT 2M

Brand: BTCINO | Manufacturer Part Number: K4005TL



Manufacturer	BTICINO
MPN / Reference	K4005TL
Catalog number	K4005TL
Category	Movement sensor complete
Minimum order	1 Pcs
Document ID	EO-C9A50E5DDB
Generated	2026-08-04

Product Overview

LN-PULS W/DOOR CONTACT 2M

Living Now touchless door push button

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTICINO > LIVING NOW**

Additional Product Information

Living Now mechanism for door control without physical contact - Detection distance: 30cm - 1000VA - to equip with front and decorative platesModel Other

Motion sensor technology Other

Constant light dimming Yes

Control de HVAC No

Forced connection No

Forced disconnection No

Animal Zone No

Creep Protection/Field Monitoring No

Background monitoring No

Networkable Yes

Optimal mounting height 1.2 m

Stair Lighting Controller No

Bypass switch Yes

Suitable for wireless streaming No

Remote control No
With remote control No
Adjustable response sensitivity Yes
Adjustable response brightness No
With signalling unit No
Learn function for responsive brightness No
Control function with control insert No
Type of mounting Recessed mounted (plaster)
Suitable for ceiling mounting No
Suitable for wall mounting No
Connection Method Screw-on terminal
Material Plastic
Material quality Thermoplastic
Halogen-free Yes
Surface treatment No treatment
Surface Finish Mate
Antibacterial treatment No
Colour Black
RAL number (similar) 9011
Transparent No
Protection Class (IP) IP20
Impact resistance IK04
Type of voltage AC
frequency 50-60 Hz
Nominal Voltage 230-230 V
Suitable for C-load No
Number of switching zones 0
Maximum starting current 2 A
Starting current min. 0.5 A
Input Extensions No
Alarm function No
With acoustic sensor No
Ambient Temperature 5-40 °C
Width 40 mm
Height 40 mm
Depth 43 mm
Mounting width 40 mm
Installation Depth 33 mm
Installation Length 40 mm
Min. depth of the recessed box 43 mm
W...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / K4005TL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.