

INDUSTRIAL COMPONENT DATA

K4037N BTCINO LN-PULS DOUBLE LOCK 10A 1M

Brand: BTCINO | Manufacturer Part Number: K4037N



Manufacturer	BTCINO
MPN / Reference	K4037N
Catalog number	K4037N
Category	Venetian blind switch/-push button
Minimum order	1 Pcs
Document ID	EO-D4C1C95069
Generated	2026-07-28

Product Overview

LN-PULS DOUBLE LOCK 10A 1M

Double push button for Living Now shutters - 10A - 250V~ - interlocked push buttons - 1 module

Double push button for Living Now blinds - 250V~ - 1mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTCINO > LIVING NOW**

Additional Product Information

Overview

Double push button 10A 250 Vac. 1 P (NA) + 1 P (NA) interlocked for roller blinds, not Backlit - 1 module.

description

Shutter mechanisms - Double push button with mechanical lock - 10 A-250 Vac - One press to activate the maneuver and when releasing it stops -To be combined with keys of 1 module ref. KG/KM/KW05 or 2 modules ref. KG/KM/KW05M2, support and decorative plate - 1 module.

specifications

For Venetian blinds Yes

For blinds Yes

For awnings No

Type of mounting Module for system interruption program, Recessed mounted (plaster)

Model 1-pole push button

Number of poles 1

Type of operation Seesaw

With electric lock No

With mechanical lock No
Mechanically Driven Yes
Electronically operated No
Material Plastic
Material quality Thermoplastic
Halogen-free Yes
Surface treatment No treatment
Surface Finish Mate
Attachment Type Lock in position
Connection Method Screw-on terminal
Colour Black
RAL number (similar) 7015
Transparent No
Label Space/Print Area No
Suitable for protection grade (IP) IP20
Nominal current 10 A
Nominal Voltage 250 V
Number of buttons 1
Number of modules (in case of modular design) 1
Device width 22 mm
Device height 45 mm
Device Depth 35 mm
Installation Depth 33 mm
Min. depth of the recessed box 43 mm
Compatible with Apple HomeKit No
Compatible with Google Assistant No
Compatible with Amazon Alexa No
Compatible IFTTT No
Impact resistance IK04
Operating Temperature -5-35 °C
Storage temperature -10-70 °C
Type of voltage AC
frequency 50-60 Hz
Lightin...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / K4037N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.