

INDUSTRIAL COMPONENT DATA

K4288C2 BTCINO LN-BASE USB TYPE-C 3A 30W 2M

Brand: BTICINO | Manufacturer Part Number: K4288C2



Manufacturer	BTICINO
MPN / Reference	K4288C2
Catalog number	K4288C2
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-F5F7C6BCDC
Generated	2026-07-28

Product Overview

LN-BASE USB TYPE-C 3A 30W 2M

Living Now USB Charger - 1 USB - Type-C - Power Delivery - 3,000 mA - 30 W - 2 modules - white

Living Now USB Charger - 1 USB - Type C - 30W- White - 2mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTICINO > LIVING NOW

Additional Product Information

Product features

USB Type-C Power Delivery Charger - Allows fast recharging of all types of devices from computers (PC - Mac), tablets (Apple - IOS Android) and smartphones (Apple / IOS Android) equipped with Power Delivery technology - Also allows the recharging of devices without Power Delivery technology (tablets and smartphones) - Power Delivery 3.0 optimizes the voltage supplied by reducing the charge cycle and preserving battery life - Energy efficiency level: VI TUV - Standby consumption: 0.06 W - Automatic output voltages: 5 - 9 - 12 -15 - 20 V - Protected against surges - Installation in recessed boxes of minimum depth 40 mm - Screw terminals of 2x2.5 mm² - Supplied without cable - To be combined with fronts ref. KG/KM/KW12C, support and embellishment plate of the Living Now series of mechanisms - 2 modules

General features

Living Now - USB charger bases

ETIM for K4288C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)
Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF000124)
Screwed terminal
Operating voltage (EF003983)
100 V
Device depth (EF008810)
41 mm
Impact strength (EF004293)
IK04
Anti-bacterial treatment (EF023790)
No
Number of ports USB-C (EF017049)
1
Min. depth of built-in installation box (EF012278)
40 mm
Output voltage (EF003933)
5 V
Power consumption (EF000346)
0.059 W
Device width (EF008808)
45 mm
Device height (EF008809)
45 mm
Colour (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / K4288C2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.