

INDUSTRIAL COMPONENT DATA

K4294C BTCINO LN-BASE USB TYPE C PD 45W 2M

Brand: BTICINO | Manufacturer Part Number: K4294C



Manufacturer	BTICINO
MPN / Reference	K4294C
Catalog number	K4294C
Category	USB power supply
Minimum order	5 Pcs
Document ID	EO-558EDF8437
Generated	2026-08-02

Product Overview

LN-BASE USB TYPE C PD 45W 2M

Living Now USB Charger - 1 USB - Type C - Power Delivery - 3000mA - 45W- 2 modules - White

Living Now USB Charger - 1 USB - Type C - 45W- White - 2mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTICINO > LIVING NOW

Additional Product Information

USB Type C Power Delivery Charger - Allows fast recharging of all types of devices from computers (PC - Mac), tablets (Apple - IOS Android) and smartphones (Apple/IOS Android) equipped with Power Delivery technology - Also allows the recharging of devices without Power Delivery technology (tablets and smartphones) - Power Delivery 3.0 optimizes the voltage supplied by reducing the charge cycle and preserving battery life - Energy efficiency level: VI TUV - Standby consumption: 0.06 W - Protected against overvoltages - Installation in recessed boxes of minimum depth 40mm - 2x2.5mm² screw terminals - Supplied without cable -To be combined with fronts ref. KG/KM/KW12PD, support and decorative plate from the Living Now series of mechanisms - 2 modules.Model Other

Number of USB-A ports 0

Number of USB-C ports 1

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-20 V

Power consumption 0.059 W

Connection Method Screw-on terminal
Type of mounting Recessed mounted (plaster)
Colour Black
RAL number 9011
Device width 45 mm
Device height 45 mm
Device Depth 41 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 33 mm
Operating Temperature -5-35 °C
Storage temperature -10-70 °C
Type of voltage AC
Power Delivery Yes
USB Power Output 45
Nominal current 1-1 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / K4294C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.