

INDUSTRIAL COMPONENT DATA

K4382 BTCINO LN-PILOT BEACONED 230V 2M

Brand: BTICINO | Manufacturer Part Number: K4382



Manufacturer	BTICINO
MPN / Reference	K4382
Catalog number	K4382
Category	Information light signal for domestic switching devices
Minimum order	5 Pcs
Document ID	EO-60CA1DE339
Generated	2026-08-02

Product Overview

LN-PILOT BEACONED 230V 2M

Pilot beaconed Living Now - 2 modules

Living Now Beaconed Pilot - 2mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTICINO > LIVING NOW

Additional Product Information

Product features

Luminous markers - Beacon pilot - 230 V~ - Allows to create a directional and decorative lighting - It is advisable to install it 30 cm from the ground - It can be controlled from a traditional mechanism or from an electronic mechanism without neutral, from a light regulator or from an automatic switch with neutral - White LED lamp, consumption 2.2 W - Luminous flux 70 lumens - Duration: 50,000 hours approx. - To be combined with front ref. KG/KM/KW71, support and embellishing plate - 2 modules

General features

Living Now - acoustic and light signalling

ETIM for K4382 Domestic wiring accessories and controls (EC000064)

Feature Name

Feature Value

Max. lamp power (EF000260)

0.5 W

Material (EF002169)

Plastic

Surface finishing (EF006569)
Matt
Lamp type (EF002423)
LED non-replaceable
Material quality (EF001257)
Thermoplastic
Halogen free (EF000025)
Yes
Type of fastening (EF002442)
Engage (snap)
Mounting method (EF000003)
Flush mounted
Nominal voltage (EF000002)
230 V
Number of modules (module system) (EF009573)
2
Transparent (EF006243)
No
Min. depth of built-in installation box (EF012278)
40 mm
Colour light source (EF001402)
White
Surface protection (EF000139)
Untreated
With light source (EF005905)
Yes
With fixed symbol/imprint (EF007949)
No
RAL-number (similar) (EF003882)
7015
With flashlight (EF006575)
No
Suitable for degree of protection (IP) (EF006755)
IP20
Device depth (EF008810)
32.5 mm
Device width (EF008808)
45 mm
Assembly arrangement (EF000005)
Basic un...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / K4382 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.