

INDUSTRIAL COMPONENT DATA**KM40 BTCINO LNWN 1M I/O SAND KEY**

Brand: BTICINO | Manufacturer Part Number: KM40



Manufacturer	BTICINO
MPN / Reference	KM40
Catalog number	KM40
Category	Control element/cover plate for domestic switching devices
Minimum order	10 Pcs
Document ID	EO-DDE7E016BA
Generated	2026-08-02

Product Overview

LNWN 1M I/O SAND KEY

Living Now bipolar switch - illuminable - 16AX - 250Vac - Sand - 1 module

Living Now w/Netatmo key for wireless stage command - Sand - 1mod

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **BTICINO > LIVING NOW WITH NETATMO****Additional Product Information**

Lighting mechanisms - Bipolar switch - 2P - 16AX - 250Vac - Automatic terminal - Becomes luminous or pilot with LED signaling lamps -To be combined with key, support and decorative plate - 1 module - Sand.Cabling System 1-pole disconnect switch

Type of operation Rocker/button

Type of mounting Module for system interruption program, Recessed mounted (plaster)

Number of modules (in case of modular design) 1

Push Button Switch Yes

Attachment Type Lock in position

With mounting plate No

Material Plastic

Material quality Thermoplastic

Halogen-free Yes

Antibacterial treatment No

Surface treatment No treatment

Surface Finish Mate
Colour Beige
RAL number (similar) 1015
Switching element color Beige
Label space/print surface No
Lighting Optional
Lighting function Orientation
Lighting Type Other
Suitable for protection grade (IP) IP21
Impact resistance IK04
Nominal Voltage 250 V
Nominal current 16 A
Monitoring contacts No
Connection Method Screw-on terminal
Heating switch No
Washing machine switch No
Device width 22 mm
Device height 45 mm
Device Depth 41 mm
Installation Depth 28 mm
Min. depth of the recessed box 38 mm
Compatible with Apple HomeKit No
Compatible with Google Assistant No
Compatible with Amazon Alexa No
Compatible IFTTT No
Operating Temperature -5-35 °C
Storage temperature -5-35 °C
Type of voltage AC
frequency 50-60 Hz
Neutral Mandatory No
Display of markings on the connection terminals No
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for KM...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / KM40 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.