

INDUSTRIAL COMPONENT DATA**KW41 BTCINO LNWN COMMAND KEY D/N 1M BL**

Brand: BTICINO | Manufacturer Part Number: KW41



Manufacturer	BTICINO
MPN / Reference	KW41
Catalog number	KW41
Category	Control element/cover plate for domestic switching devices
Minimum order	1 Pcs
Document ID	EO-DF5A871F0D
Generated	2026-08-01

Product Overview

LNWN COMMAND KEY D/N 1M BL

2P+T Living Now Base - Italian Standard - Screw Connection - White - 1 module

Living Now w/Netatmo key for wireless command "Day/Night" - White - 1mod

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **BTICINO > LIVING NOW WITH NETATMO****Additional Product Information**

Italian standard 2P+T bases - 10A - 250 Vac - Distance between alveoli of 19mm - Screw connection - With protection shutters - 1 module -To be combined with KW02 front, support and decorative plate - White.Model Italian Type P11

Protective contact Round

Number of active (round) contacts 1

Number of active contacts (drawings) 0

Type of mounting Basic element with center cover plate, Recessed mounted (plaster)

With signal lamp No

Number of USB-A ports 0

Number of USB-C ports 0

Number of sockets 1

Phase-separated power outlets No

Number of modules (in case of modular design) 1

Number of interchangeable sockets 0

Number of phases 1

Printing/Marking Other
Connection Method Screw-on terminal
With flip-top lid No
With enhanced contact protection Yes
Label Space/Print Area No
Colour White
RAL number (similar) 9003
Metallic color No
Transparent No
Lockable No
Expulsion mechanism No
Isolated installation No
With functional lighting No
With adjustable lighting No
Surge protection No
Residual Current Device No
With microfusion No
Special power supply none
Attachment Type Hemming
Material Plastic
Material quality Thermoplastic
Halogen-free Yes
Surface treatment No treatment
Surface Finish Mate
Antibacterial treatment No
With loop function No
With on/off switch No
Rotated center insert No
Nominal intensity 10 A
Nominal Voltage 250 V
frequency 45-55 Hz
Suitable for protection grade (IP) IP20
Impact resistance Other
Device width 22 mm
Device height 45 mm
Device Depth 38 mm
Min. depth of the...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / KW41 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.