

**INDUSTRIAL COMPONENT DATA**

# KW4286CW2 BTCINO LN-BASE USBA 3A/5V+INDUC. WHITE

Brand: BTCINO | Manufacturer Part Number: KW4286CW2



|                 |                  |
|-----------------|------------------|
| Manufacturer    | BTCINO           |
| MPN / Reference | KW4286CW2        |
| Catalog number  | KW4286CW2        |
| Category        | USB power supply |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-1A420F85D1    |
| Generated       | 2026-07-28       |

## Product Overview

LN-BASE USBA 3A/5V+INDUC. WHITE

Induction Charger Dock + Living Now USB Type-A Dock - White - 2 Modules

Induction charging base + USB Type A base Living Now - White - 2mod

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                     |
|--------------|---------------------|
| Catalog path | BTCINO > LIVING NOW |
|--------------|---------------------|

## Additional Product Information

**Product features**

Universal induction and USB chargers - Induction charging: 1 A - USB type A - 3 A - 5 V - 230 Vac - Allows fast and wireless recharging of a smartphone equipped with an induction receiver - Adapter to bed headboards and workspaces - According to the WPC Qi (Wireless Power Consortium) standard - According to the EN- 62479 standard (EMC emission) - Anti-theft lock function - Possibility of mounting in horizontal multi-position - Dimensions 136.5 x 70 x 56.5 mm - To be combined with bracket and trim plate - 2 modules - White

General features

Living Now - induction charger bases

ETIM for KW4286CW2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Module frame/grid

Suitable for degree of protection (IP) (EF006755)

IP40

Connection type (EF000124)

Screwed terminal

Operating voltage (EF003983)

110 V

Device depth (EF008810)

60 mm

Impact strength (EF004293)

IK04

Anti-bacterial treatment (EF023790)

No

Min. depth of built-in installation box (EF012278)

43 mm

Device width (EF008808)

70 mm

Device height (EF008809)

136 mm

Colour (EF000007)

White

RAL-number (EF000116)

9003

Max. output current (EF001315)

3000 mA

Frequency (EF000416)

50 Hz

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / KW4286CW2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.