

INDUSTRIAL COMPONENT DATA

L4142 BTCINO LL-BASE-FR 2P+T 16A 2M ANTR

Brand: BTCINO | Manufacturer Part Number: L4142



Manufacturer	BTCINO
MPN / Reference	L4142
Catalog number	L4142
Category	Socket outlet
Minimum order	10 Pcs
Document ID	EO-9CBCCE8BCD
Generated	2026-08-02

Product Overview

LL-BASE-FR 2P+T 16A 2M ANTR

2P+T Livinglight - standard French - connection by screws - Anthracite - 2 modules

2P+T Livinglight Base - French Standard - Anthracite - 2mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTCINO > LIVINGLIGHT MECHANISMS**

Additional Product Information

Product features

Bases 2P+T French standard 16 A - 250 V~ - Connection by screws - With shutter protection - Is converted into luminous pilot lamps ref. LN4742V230 - 2 modules - Anthracite General characteristics

Livinglight - bases of power

ETIM for L4142 Domestic wiring accessories and controls (EC000125)

Feature Name

Feature Value

Over voltage protection (EF001332)

No

Nominal current (EF000001)

16 A

Rotated central insert (EF001331)

No

Material quality (EF001257)

Thermoplastic
Mounting method (EF000003)
Flush mounted
Special power supply (EF001334)
EV006426
Connection type (EF000124)
Screw terminal
Fault current protection (EF001333)
No
Nominal voltage (EF000002)
250 V
Number of modules (module system) (EF009573)
2
Compatible with Apple HomeKit (EF014925)
No
Eject-mechanism (EF001051)
No
Compatible with Amazon Alexa (EF014927)
No
Compatible with Google Assistant (EF014926)
No
Number of ports USB-C (EF017049)
0
Min. depth of built-in installation box (EF012278)
40 mm
Imprint/indication (EF003823)
None
With hinged lid (EF000117)
No
Number of ports USB-A (EF000997)
0
Metallic colour (EF015260)
No
With Wi-Fi signal repeater (EF013509)
No
RAL-number (similar) (EF003882)
7016
Model (EF000010)
Earthing pin
Number of socket outlets switchable (EF008814)
0
Suitable for degree of protection (IP) (EF006755)
IP20
Device depth (EF008810)
41 mm
Impact strength (EF004293)
IK00

Anti-bacterial treatment (EF023790)

No

Number of active contacts (square) (EF017115)

0

Protective contact (EF...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / L4142 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.