

INDUSTRIAL COMPONENT DATA

L4286C2 BTCINO LL-BASE USB C+C 3A/5V 2M ANTR

Brand: BTCINO | Manufacturer Part Number: L4286C2



Manufacturer	BTCINO
MPN / Reference	L4286C2
Catalog number	L4286C2
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-7C50B69264
Generated	2026-08-02

Product Overview

LL-BASE USB C+C 3A/5V 2M ANTR

Base USB charger (C+C) Livinglight - 3 To - 5 V - 230 V - 2 modules - Anthracite

USB (C+C) Livinglight Charger Base - 3A - 5V - 230V - 2mod - Anthracite

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTCINO > LIVINGLIGHT MECHANISMS

Additional Product Information

Product features

Universal chargers USB - Compliant to the standard IEC 62684-2011-01 - Allow the quick charging of mobile phones, tablets, smartphones, MP3, MP4 - Release space for bases of power - Consumption standby < 0.1 W - Class II TBTS - According to the EEC directive on the harmonization of the standard recharging of portable terminals and the reduction of chargers, mobile - Supplied without cable - 5 V - 230 V - Charger dual-USB 3 A - Type C + C - 2 modules - Anthracite

General characteristics

Livinglight - USB chargers

ETIM for L4286C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted

Suitable for degree of protection (IP) (EF006755)

IP40

Connection type (EF000124)

Screwed terminal

Operating voltage (EF003983)

100 V

Device depth (EF008810)

43 mm

Impact strength (EF004293)

IK04

Anti-bacterial treatment (EF023790)

No

Number of ports USB-C (EF017049)

2

Min. depth of built-in installation box (EF012278)

42 mm

Output voltage (EF003933)

5 V

Power consumption (EF000346)

0.064 W

Device width (EF008808)

44 mm

Device height (EF008809)

44 mm

Colour (EF000007)

Anthracite

Number of ports USB-A (EF000997)

0

RAL-number (EF000116)

7015

Max. output current (EF001315)

3000 mA

Frequency (EF000416)

50 Hz

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / L4286C2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.