

**INDUSTRIAL COMPONENT DATA****L4305/16 BTCINO LL-M+DIF 1P+N 16A 10MA 2M ANTR**

Brand: BTCINO | Manufacturer Part Number: L4305/16

PRODUCT IMAGE\n\nNOT  
AVAILABLE

|                 |                               |
|-----------------|-------------------------------|
| Manufacturer    | BTICINO                       |
| MPN / Reference | L4305/16                      |
| Catalog number  | L4305/16                      |
| Category        | Earth leakage circuit breaker |
| Minimum order   | 1 Pcs                         |
| Document ID     | EO-D5409316C2                 |
| Generated       | 2026-08-04                    |

**Product Overview**

LL-M+DIF 1P+N 16A 10MA 2M ANTR

Circuit breaker circuit breaker + differential Livinglight - 16 A - 2 modules - Anthracite

Livinglight magnet + diff automatic switch - 16A - 2mod - Anthracite

**STRUCTURED PRODUCT DATA****Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

**Classification & Catalog Path**Catalog path **BTICINO > LIVINGLIGHT MECHANISMS****Additional Product Information**

## Product features

Circuit breakers residual current protection and differential - Features a shaded pole - Indicator of contacts open and closed

- Push-to-test - To 16 - Power of court: 3,000 - 2 modules - Anthracite General characteristics

Livinglight - lighting, buoys, signaling and security

ETIM for L4305/16 Circuit breakers and fuses (EC000905)

Feature Name

Feature Value

Frequency (EF005455)

50/60 Hz

Connectable conductor cross section solid-core (EF007337)

2.5 mm<sup>2</sup>

Ambient temperature during operating (EF007515)

-5 °C

Degree of protection (IP) (EF005474)

IP20

Leakage current type (EF002560)

Other

Concurrently switching neutral conductor (EF005997)

Yes

Rated short-circuit breaking capacity according to IEC 60947-2 (EF006065)

3 kA

Rated short-circuit breaking capacity according to EN 61009 (EF012628)

3 kA

Rated short-circuit breaking capacity I<sub>cn</sub> according to EN 61009-1 (EF011981)

3 kA

Number of protected poles (EF005548)

1

Built-in depth (EF000218)

33.5 mm

Number of poles (total) (EF008618)

1

Rated current (EF000227)

16 A

Current limiting class (EF002568)

1

Release characteristic (EF000889)

C

Rated voltage (EF000228)

230 V

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / L4305/16 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.