

INDUSTRIAL COMPONENT DATA

N4180 BTCINO LL-IT BASE 2P+T 16A 1M WHITE

Brand: BTCINO | Manufacturer Part Number: N4180



Manufacturer	BTCINO
MPN / Reference	N4180
Catalog number	N4180
Category	Socket outlet
Minimum order	5 Pcs
Document ID	EO-3394BF9736
Generated	2026-07-31

Product Overview

LL-IT BASE 2P+T 16A 1M WHITE

LL-BASE IT 2P+T 16A 1M WHITE

2P+T Livinglight - standard Italian - connection by screws - White - 1 module

2P+T Livinglight Base - Italian Standard - White - 1mod

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTCINO > LIVINGLIGHT MECHANISMS

Additional Product Information

Product features

Bases 2P+T standard Italian - 16 A - 250 V~ - Distance between sockets 19 mm and 26 mm - Connection by screws - With shutter protection - 1 module - White General characteristics

Livinglight - bases of power

ETIM for N4180 Domestic wiring accessories and controls (EC000125)

Feature Name

Feature Value

Over voltage protection (EF001332)

No

Nominal current (EF000001)

16 A

Rotated central insert (EF001331)

No

Material quality (EF001257)
Thermoplastic
Mounting method (EF000003)
Flush mounted
Special power supply (EF001334)
EV006426
Connection type (EF000124)
Screwed terminal
Fault current protection (EF001333)
No
Nominal voltage (EF000002)
250 V
Number of modules (module system) (EF009573)
1
Compatible with Apple HomeKit (EF014925)
No
Eject-mechanism (EF001051)
No
Compatible with Amazon Alexa (EF014927)
No
Compatible with Google Assistant (EF014926)
No
Number of ports USB-C (EF017049)
0
Min. depth of built-in installation box (EF012278)
36 mm
Imprint/indication (EF003823)
None
With hinged lid (EF000117)
No
Number of ports USB-A (EF000997)
0
Metallic colour (EF015260)
No
With Wi-Fi signal repeater (EF013509)
No
RAL-number (similar) (EF003882)
9016
Model (EF000010)
Italian type Bipasso
Number of socket outlets switchable (EF008814)
0
Suitable for degree of protection (IP) (EF006755)
IP20
Device depth (EF008810)
37 mm
Impact strength (EF004293)

IK00

Anti-bacterial treatment (EF023790)

No

Protective contact (EF017116)

Round

Device width (EF008808)

22 mm

With on/off s...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / N4180 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.