

INDUSTRIAL COMPONENT DATA

N4288C2 BTCINO LL-BASE USB TYPE-C 3A 30W BLAN

Brand: BTCINO | Manufacturer Part Number: N4288C2



Manufacturer	BTCINO
MPN / Reference	N4288C2
Catalog number	N4288C2
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-D4B79B2022
Generated	2026-07-28

Product Overview

LL-BASE USB TYPE-C 3A 30W BLAN

USB Livinglight Base - 1 USB - Type-C - Power Delivery - 3.0000mA - 30W - 2 modules - White

USB Livinglight Base - 1 USB Type C - 30W - 2mod - White

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTCINO > LIVINGLIGHT MECHANISMS

Additional Product Information

Product features

The USB Type-C charger allows fast charging of mobile devices (tablets, smartphones, MP3 players, watches, etc.).

General features

USB Type-C Charger Power Delivery - Allows fast recharging of all types of devices from computers (PC - Mac), tablets (Apple - IOS Android) and smartphones (Apple / IOS Android) equipped with Power Delivery technology - Also allows the recharging of devices without Power Delivery technology (tablets and smartphones) - Power Delivery 3.0 optimizes the voltage supplied by reducing the charge cycle and preserving battery life - Level of energy efficiency: VI TUV - Standby consumption: 0.06 W - Automatic output voltages: 5 - 9 - 12 -15 - 20 V - Protected against surges - Installation in flush boxes with a minimum depth of 40 mm - 2x2.5 mm² screw terminals - Supplied without cable

ETIM for N4288C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted

Suitable for degree of protection (IP) (EF006755)

IP40

Connection type (EF000124)

Screwed terminal

Operating voltage (EF003983)

100 V

Device depth (EF008810)

45.6 mm

Impact strength (EF004293)

IK04

Anti-bacterial treatment (EF023790)

No

Number of ports USB-C (EF017049)

1

Min. depth of built-in installation box (EF012278)

40 mm

Output voltage (EF003933)

5 V

Power consumption (EF000346)

0.059 W

Device width (EF008808)

43.8 mm

Device height (EF008809)

47 mm

Colour (EF000007)

White

Number of ports USB-A (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / N4288C2 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.