

## INDUSTRIAL COMPONENT DATA

## NT4005TL BTCINO LL-PULS S/CONT. 2M TECH DOOR

Brand: BTCINO | Manufacturer Part Number: NT4005TL



|                 |                          |
|-----------------|--------------------------|
| Manufacturer    | BTCINO                   |
| MPN / Reference | NT4005TL                 |
| Catalog number  | NT4005TL                 |
| Category        | Movement sensor complete |
| Minimum order   | 1 Pcs                    |
| Document ID     | EO-A5459B5D32            |
| Generated       | 2026-08-03               |

## Product Overview

LL-PULS S/CONT. 2M TECH DOOR

Touchless push button for Livinglight doorsAluminium

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path BTCINO &gt; LIVINGLIGHT MECHANISMS

## Additional Product Information

Mechanism for door control without physical contact Livinglight - Detection distance: 30cm - 1000VA - supplied with finished front, to equip with decorative platesModel Other

Motion sensor technology Other

Constant light dimming Yes

Control de HVAC No

Forced connection No

Forced disconnection No

Animal Zone No

Creep Protection/Field Monitoring No

Background monitoring No

Networkable Yes

Optimal mounting height 1.2 m

Stair Lighting Controller No

Bypass switch Yes

Suitable for wireless streaming No

Remote control No  
With remote control No  
Adjustable response sensitivity Yes  
Adjustable response brightness No  
With signalling unit No  
Learn function for responsive brightness No  
Control function with control insert No  
Type of mounting Recessed mounted (plaster)  
Suitable for ceiling mounting No  
Suitable for wall mounting No  
Connection Method Screw-on terminal  
Material Plastic  
Material quality Thermoplastic  
Halogen-free Yes  
Surface treatment Varnishing  
Surface Finish Mate  
Antibacterial treatment No  
Colour aluminium  
RAL number (similar) 7035  
Transparent No  
Protection Class (IP) IP20  
Impact resistance IK04  
Type of voltage AC  
frequency 50-60 Hz  
Nominal Voltage 230-230 V  
Suitable for C-load No  
Number of switching zones 0  
Maximum starting current 2 A  
Starting current min. 0.5 A  
Input Extensions No  
Alarm function No  
With acoustic sensor No  
Ambient Temperature 5-40 °C  
Width 40 mm  
Height 40 mm  
Depth 43 mm  
Mounting width 40 mm  
Installation Depth 33 mm  
Installation Length 40 mm  
Min. depth of t...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / NT4005TL with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.