

INDUSTRIAL COMPONENT DATA

NT4191A BTCINO LL-BASE USB TO 3A/5V 1M TECH

Brand: BTICINO | Manufacturer Part Number: NT4191A



Manufacturer	BTICINO
MPN / Reference	NT4191A
Catalog number	NT4191A
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-9C4899073E
Generated	2026-08-01

Product Overview

LL-BASE USB TO 3A/5V 1M TECH

Livinglight USB Single Charger Base - Type A - Tech - 1 module

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTICINO > LIVINGLIGHT MECHANISMS**

Additional Product Information

Overview

USBA Chargers - 3A/5V - 15W - Allow fast charging of mobiles, tablets, smartphones, MP3, MP4 - Free up space for power bases - Standby consumption 0.1 W - Class II TBTS - Supplied without cable - 1 module - Tech.

specifications

Model Other

Number of USB-A ports 1

Number of USB-C ports 0

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-5 V

Power consumption 0.069 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)

Colour aluminium

RAL number 7035
Device width 22 mm
Device height 44 mm
Device Depth 41 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 30 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Nominal Voltage 100-240 V
Power Delivery No
Nominal current 0.5-0.5 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross-section 1.5-2.5 mm²
ETIM for NT4191A Domestic wiring accessories and controls (EC002949)
Feature Name
Feature Value
Model (EF000010)
Other
Mounting method (EF000003)
Flush mounted
Suitable for degree of protection (IP) (EF006755)
IP40
Connection type (EF000124)
Screw terminal
Operating voltage (EF003983)
100 V
Device depth (EF008810)
41 mm
Im...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / NT4191A with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.