

## INDUSTRIAL COMPONENT DATA

## NT4285C2 BTCINO LL-BASE USBA+2.4 A/5V 2M TECH

Brand: BTICINO | Manufacturer Part Number: NT4285C2



|                 |                  |
|-----------------|------------------|
| Manufacturer    | BTICINO          |
| MPN / Reference | NT4285C2         |
| Catalog number  | NT4285C2         |
| Category        | USB power supply |
| Minimum order   | 1 Pcs            |
| Document ID     | EO-57BC858A37    |
| Generated       | 2026-07-28       |

## Product Overview

LL-BASE USBA+2.4 A/5V 2M TECH

Base charger dual USB Livinglight - 2.4 A - 5 V - 230 V - Tech - 2 modules

USB Charger Base A+A Livinglight - 2.4A - 5V - 230V - Tech - 2mod

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification &amp; Catalog Path

Catalog path BTICINO &gt; LIVINGLIGHT MECHANISMS

## Additional Product Information

## Product features

Universal chargers USB - Compliant to the standard IEC 62684-2011-01 - Allow the quick charging of mobile phones, tablets, smartphones, MP3, MP4 - Release space for bases of power - Consumption standby < 0.1 W - Class II TBTS - According to the EEC directive on the harmonization of the standard recharging of portable terminals and the reduction of chargers, mobile - Supplied without cable - 5 V - 230 V Charger double USB 2.400 mA - 2 modules - Tech General characteristics

Livinglight - bases of power

ETIM for NT4285C2 Domestic wiring accessories and controls (EC002949)

Feature Name

Feature Value

Model (EF000010)

Other

Mounting method (EF000003)

Flush mounted

Suitable for degree of protection (IP) (EF006755)

IP40

Connection type (EF000124)

Screwed terminal

Operating voltage (EF003983)

100 V

Device depth (EF008810)

43 mm

Impact strength (EF004293)

IK04

Anti-bacterial treatment (EF023790)

No

Number of ports USB-C (EF017049)

0

Min. depth of built-in installation box (EF012278)

40 mm

Output voltage (EF003933)

5 V

Power consumption (EF000346)

0.068 W

Device width (EF008808)

44 mm

Device height (EF008809)

44 mm

Colour (EF000007)

Aluminium

Number of ports USB-A (EF000997)

2

RAL-number (EF000116)

7035

Max. output current (EF001315)

3000 mA

Frequency (EF000416)

50 Hz

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / NT4285C2 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.