

INDUSTRIAL COMPONENT DATA**NT4294C BTCINO LL-BASE USB C PD 45W 2M TECH**

Brand: BTICINO | Manufacturer Part Number: NT4294C



Manufacturer	BTICINO
MPN / Reference	NT4294C
Catalog number	NT4294C
Category	USB power supply
Minimum order	1 Pcs
Document ID	EO-64A0A0AAB0
Generated	2026-07-31

Product Overview

LL-BASE USB C PD 45W 2M TECH

Livinglight USB Charger - 1 USB Type C - Power Delivery - 3000mA - 45W- 2 modules - Tech

Livinglight USB Charger - 1 USB Type C - 45W- 2mod - Tech

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	BTICINO > LIVINGLIGHT MECHANISMS
--------------	----------------------------------

Additional Product Information

USB Type C Power Delivery Charger - Allows fast recharging of all types of devices from computers (PC - Mac), tablets (Apple - IOS Android) and smartphones (Apple/IOS Android) equipped with Power Delivery technology - Also allows the recharging of devices without Power Delivery technology (tablets and smartphones) - Power Delivery 3.0 optimizes the voltage supplied by reducing the charge cycle and preserving battery life - Energy efficiency level: VI TUV - Standby consumption: 0.06 W - Protected against overvoltages - Installation in recessed boxes of minimum depth 40mm - Screw terminals of 2x2.5mm² - Supplied without cable.Model Other

Number of USB-A ports 0

Number of USB-C ports 1

Operating voltage 100-240 V

frequency 50-60 Hz

Maximum output current 3000 mA

Output voltage 5-20 V

Power consumption 0.059 W

Connection Method Screw-on terminal

Type of mounting Recessed mounted (plaster)
Colour aluminium
RAL number 7035
Device width 43.8 mm
Device height 47 mm
Device Depth 45.6 mm
Min. depth of the recessed box 40 mm
Suitable for protection grade (IP) IP40
Impact resistance IK04
Antibacterial treatment No
Wireless No
Installation Depth 34.6 mm
Operating Temperature 5-40 °C
Storage temperature -20-70 °C
Type of voltage AC
Power Delivery Yes
USB Power Output 45
Nominal current 1-1 A
Neutral Mandatory Yes
Display of markings on the connection terminals Yes
Compliant with commissioning tests (1000 V) No
Halogen-free Yes
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / NT4294C with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.