

INDUSTRIAL COMPONENT DATA**NT4305/10 BTCINO LL-M+DIFF 1P+N 10A 10MA 2M TECH**

Brand: BTICINO | Manufacturer Part Number: NT4305/10

PRODUCT IMAGE\nNOT
AVAILABLE

Manufacturer	BTICINO
MPN / Reference	NT4305/10
Catalog number	NT4305/10
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-1A87241D78
Generated	2026-08-02

Product Overview

LL-M+DIFF 1P+N 10A 10MA 2M TECH

Circuit breaker circuit breaker + differential Livinglight - 10 A - 2 modules - Tech

Livinglight magnet + diff automatic switch - 10A - 2mod - Tech

STRUCTURED PRODUCT DATA**Technical Specifications**

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog PathCatalog path **BTICINO > LIVINGLIGHT MECHANISMS****Additional Product Information****Product features**

Circuit breakers residual current protection and differential - Features a shaded pole - Indicator of contacts open and closed

- Push-to-test - 10 - Power of court: 3,000 - 2 modules - Tech General characteristics

Livinglight - lighting, buoys, signaling and security

ETIM for NT4305/10 Circuit breakers and fuses (EC000905)

Feature Name

Feature Value

Frequency (EF005455)

50/60 Hz

Connectable conductor cross section solid-core (EF007337)

2.5 mm²

Ambient temperature during operating (EF007515)

-5 °C

Degree of protection (IP) (EF005474)

IP20

Leakage current type (EF002560)

Other

Concurrently switching neutral conductor (EF005997)

Yes

Rated short-circuit breaking capacity according to IEC 60947-2 (EF006065)

3 kA

Rated short-circuit breaking capacity according to EN 61009 (EF012628)

3 kA

Rated short-circuit breaking capacity I_{cn} according to EN 61009-1 (EF011981)

3 kA

Rated fault current (EF002358)

0.01 A

Number of protected poles (EF005548)

1

Built-in depth (EF000218)

33.5 mm

Number of poles (total) (EF008618)

1

Rated current (EF000227)

10 A

Current limiting class (EF002568)

1

Release characteristic (EF000889)

C

Rated voltage (EF000228)

230 V

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / NT4305/10 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.