

INDUSTRIAL COMPONENT DATA

NT4431N BTCINO LL-IR SENSOR 2A 1M TECH

Brand: BTICINO | Manufacturer Part Number: NT4431N



Manufacturer	BTICINO
MPN / Reference	NT4431N
Catalog number	NT4431N
Category	Movement sensor complete
Minimum order	1 Pcs
Document ID	EO-FDE42CC552
Generated	2026-08-01

Product Overview

LL-IR SENSOR 2A 1M TECH

LL-SENSOR IR 2A 1M TECH

Automatic switch to GO to 2ND Livinglight - 1 module - Tech

Livinglight 2A IR Automatic Switch - 1mod - Tech

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTICINO > AUTONOMOUS LIGHTING MANAGEMENT

Additional Product Information

Product features

Switches to passive Infrared - Switch with motion detection to GO passive - Circuit of a twilight switch with a threshold variable with possibility of exclusion - Circuit timing adjustable from 30 seconds to 10 minutes - relay Output 2 A resistive/inductive, 0.5 A fluorescence/LED, 2 TO the cos ϕ = 0.5 motors 230 Vac - Power supply 230 Vac - 3-wire - 1 module - Tech General characteristics

Livinglight - detectors

ETIM for NT4431N Domestic wiring accessories and controls (EC000133)

Feature Name

Feature Value

Height (EF000040)

51 mm

With remote control (EF000483)

No

Bridging switch (EF001099)

No

Staircase light controller (EF001098)

Yes

Material quality (EF001257)

Thermoplastic

Mounting method (EF000003)

Flush mounted

Min. switch-on time (EF006589)

30 s

Compatible with Apple HomeKit (EF014925)

No

Detection angle horizontal (EF006582)

-30 °

Compatible with Amazon Alexa (EF014927)

No

Compatible with Google Assistant (EF014926)

No

Response value sensitivity adjustable (EF003429)

Yes

Animal zone (EF006311)

No

Model (EF000010)

Movement sensor

With alarm function (EF005624)

No

Optimum mounting height (EF008011)

120 m

Max. duty cycle (EF006590)

600 min

Anti-bacterial treatment (EF023790)

No

With acoustic sensor (EF017675)

No

Background monitoring (EF017674)

No

Max. starting current (EF001732)

2 A

Connection cable length (EF003636)

0 mm

Depth (EF000049)

47 mm

Temperature (EF001731)

5 °C

Substation input (EF003876)

No

Suitable for C-load (EF003832)

No

Colour (EF000007)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend BTICINO / NT4431N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.