

INDUSTRIAL COMPONENT DATA

RA4003TL BTICINO CL-CONM W/CONTACT LIGHT 2M ALU

Brand: BTICINO | Manufacturer Part Number: RA4003TL



Manufacturer	BTICINO
MPN / Reference	RA4003TL
Catalog number	RA4003TL
Category	Movement sensor complete
Minimum order	1 Pcs
Document ID	EO-C27BD4F30A
Generated	2026-08-04

Product Overview

CL-CONM W/CONTACT LIGHT 2M ALU
Classia Lighting Contactless SwitchAluminum

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	BTICINO
--------------	---------

Additional Product Information

Classia mechanisms for non-physical contact lighting - Detection distance: 6cm - supplied with finishing front, to equip with decorative platesModel Other
Motion sensor technology Other
Constant light dimming Yes
Control de HVAC No
Forced connection No
Forced disconnection No
Animal Zone No
Creep Protection/Field Monitoring No
Background monitoring No
Networkable Yes
Optimal mounting height 1.2 m
Stair Lighting Controller No
Bypass switch Yes
Suitable for wireless streaming No

Remote control No
With remote control No
Adjustable response sensitivity Yes
Adjustable response brightness No
With signalling unit No
Learn function for responsive brightness No
Control function with control insert No
Type of mounting Recessed mounted (plaster)
Suitable for ceiling mounting No
Suitable for wall mounting No
Connection Method Screw-on terminal
Material Plastic
Material quality Thermoplastic
Halogen-free Yes
Surface treatment No treatment
Surface Finish Mate
Antibacterial treatment No
Colour aluminium
RAL number (similar) 7035
Transparent No
Protection Class (IP) IP20
Impact resistance IK04
Type of voltage AC
frequency 50-60 Hz
Nominal Voltage 230-230 V
Suitable for C-load No
Number of switching zones 0
Maximum starting current 2 A
Starting current min. 0.5 A
Input Extensions No
Alarm function No
With acoustic sensor No
Ambient Temperature 5-40 °C
Width 40 mm
Height 40 mm
Depth 43 mm
Mounting width 40 mm
Installation Depth 33 mm
Installation Length 40 mm
Min. depth of the recessed box 43...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / RA4003TL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.