

INDUSTRIAL COMPONENT DATA

YD4003TL BTCINO LW-CONM S/ CONTACT LIGHT 2M DK

Brand: BTCINO | Manufacturer Part Number: YD4003TL



Manufacturer	BTICINO
MPN / Reference	YD4003TL
Catalog number	YD4003TL
Category	Movement sensor complete
Minimum order	1 Pcs
Document ID	EO-5FCDCE758B
Generated	2026-08-03

Product Overview

LW-CONM S/ CONTACT LIGHT 2M DK

Light Now Touchless Lighting Mechanism - 2 Modules - Dark

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **BTICINO > MATIX MECHANISMS**

Additional Product Information

Mechanisms for non-physical contact lighting Light Now - Detection distance: 6cm - with LED pilot activated by default (can be deactivated) - to equip with support and decorative plates It can be wired with or without neutral. 4 modes available: switch/switch/master-slave/pushbutton modeModel Other

Motion sensor technology Other

Constant light dimming No

Control de HVAC No

Forced connection No

Forced disconnection No

Animal Zone No

Creep Protection/Field Monitoring No

Background monitoring No

Networkable Yes

Scanning angle 0 °

Optimal mounting height 3 /

Stair Lighting Controller No

Bypass switch Yes
Side reach 0 m
Detection field presence max. 0 m²
Front Reach 0 m
Ground Sensing Diameter 0 m
Suitable for wireless streaming No
Remote control No
With remote control No
Adjustable response sensitivity Yes
Adjustable response brightness No
With signalling unit No
Learn function for responsive brightness No
Control function with control insert No
Type of mounting Recessed mounted (plaster)
Suitable for ceiling mounting No
Suitable for wall mounting Yes
Connection Method Screw-on terminal
Material Plastic
Material quality Thermoplastic
Halogen-free Yes
Surface treatment Varnishing
Surface Finish Mate
Antibacterial treatment No
Colour Black
RAL number (similar) 9011
Transparent Yes
Protection Class (IP) IP20
Impact resistance IK04
Type of voltage AC
frequency 50-60 Hz
Nominal Voltage 230-230 V
Minimum duty cycle 0 seconds
Maximum duty cycle 0 min
Shutdown delay 0 seconds
Power-on d...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / YD4003TL with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.