

INDUSTRIAL COMPONENT DATA

YD4027N BTCINO LW-CONM DOUBLE 10AX 1M DK

Brand: BTICINO | Manufacturer Part Number: YD4027N



Manufacturer	BTICINO
MPN / Reference	YD4027N
Catalog number	YD4027N
Category	Venetian blind switch/-push button
Minimum order	1 Pcs
Document ID	EO-0666EC90F1
Generated	2026-07-29

Product Overview

LW-CONM DOUBLE 10AX 1M DK

Double switch for Light Now blinds - 1 module - Dark

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path BTICINO > MATIX MECHANISMS

Additional Product Information

Shutter mechanisms - Double switch - 10 AX-250 Vac - One press to activate the maneuver, another press in the center to stop it - not illuminable - To be combined with support and decorative plate - 1 module. For Venetian blinds Yes

For blinds Yes

For awnings No

Type of mounting Module for system interruption program, Recessed mounted (plaster)

Model 1-pole switch

Number of poles 1

Type of operation Other

With electric lock No

With mechanical latch No

Mechanically Driven Yes

Electronically operated No

Material Plastic

Material quality Thermoplastic

Halogen-free Yes

Surface treatment Varnishing
Surface Finish Mate
Attachment Type Lock in position
Connection Method Screw-on terminal
Colour Black
RAL number (similar) 9011
Transparent Yes
Label Space/Print Area No
Suitable for protection grade (IP) IP20
Nominal current 10 A
Nominal Voltage 250 V
Number of buttons 1
Number of modules (in case of modular design) 1
Device width 22.5 mm
Device height 45 mm
Device Depth 36.5 mm
Installation Depth 28.5 mm
Min. depth of the recessed box 38.5 mm
Compatible with Apple HomeKit No
Compatible with Google Assistant No
Compatible with Amazon Alexa No
Compatible IFTTT No
Impact resistance IK04
Operating Temperature -5-35 °C
Storage temperature -10-70 °C
Type of voltage AC
frequency 50-60 Hz
Lighting Type Not included
Display of markings on the connection terminals No
Antibacterial treatment No
Number of terminals 2
Terminal capacity 1.5-2.5 mm²
Connection Cable Type Flexible or rigid
Core cross...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send BTICINO / YD4027N with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.